

List of Figures

Figures	Title	page
1.1	Commercial hydrogen applications (Source: i Popular Mechanics, 2016 ; ii BMW, 2016; iii Picture Newsletter, 2016; iv Fuel Cell Markets, 2016)	2
1.2	Gas sensor classification based on sensing mechanism (Source: Liu <i>et al.</i> , 2012)	3
1.3	Energy band model for metal oxide semiconductor grains of compressed power where qV_s is barrier height between two grains (Source: Sharma and Madou, 2012)	8
1.4	Hydrogen sensing mechanism for metal oxide semiconductor sensor (Source: Gu <i>et al.</i> , 2012)	8
1.5	Pictorial representation of gas sensing: (a) Compact layer and (b) Porous layer (Source: Sharma and Madou, 2012)	9
1.6	Energy band diagram of metal and n-type semiconductor contact: (a) Before equilibrium and (b) After equilibrium (Sze and Ng, 2007)	10
1.7	Lowering Schottky barrier due to hydrogen in energy band diagram for metal semiconductors	12
2.1	Pictorial representation of RF sputtering technique	20
2.2	Experimental setup of RF sputtering (Hind High Vacuum combined RF/DC sputtering system)	21
2.3	Pictorial representation of thermal evaporation system	22
2.4	Experimental setup of thermal evaporation system (Semi-core Thermal/e-Beam evaporation system)	22
2.5	Schematic diagram of gamma exposer chamber for gamma irradiation (Source: Barala <i>et al.</i> , 2015)	23
2.6	Schematic diagram of chamber of a 15 UD pelletron accelerator at IUAC, New Delhi (Source: IUAC, New Delhi)	24
2.7	Schematic diagram of bragg's x-ray diffraction	25
2.8	X-Ray Diffraction System (D8 Advance, Bruker)	25
2.9	Schematic diagram of AFM imaging	26
2.10	Instrument setup for AFM at IIT Jodhpur (Park XE-70)	26
2.11	Schematic diagram of FESEM characterization	27
2.12	JEOL JSM-7100F FESEM instrument (Source: University of Nova Gorica, Slovenia / Material Research Lab)	28
2.13	Schematic diagram of CL spectroscopy (Source: Furukawa <i>et al.</i> , 2013)	28
2.14	Working principle of PL spectroscopy	29
2.15	Schematic diagram of raman spectroscopy	30
2.16	Experimental setup for electrical characterization at IIT Jodhpur	30
2.17	Customized gas sensing setup used at IIT Jodhpur	31
3.1	Schematic diagrams of three basic models for initial nucleation in thin film deposition	34
3.2	X-ray diffraction spectra of ZnO thin film on n-Si substrate with growth temperature varying from RT to 400 °C	36
3.3	Variation of FWHM ₍₀₀₂₎ and peak position $2\theta_{(002)}$ (degree) with substrate temperature changing from RT to 400 °C	37
3.4	Linear relationship between lattice constant and bi-axial stress on substrate temperature	39
3.5	(a-e) AFM images of deposited nano-crystalline ZnO thin films at various growth substrate temperature varying from RT to 400 °C	40
3.6	RMS roughness of deposited ZnO thin films as deposition temperature increases from RT to 400 °C	41
3.7	(a-d) Top view of FESEM images of ZnO thin films with various deposition temperature ranging from RT, 200 °C, 300 °C, 400 °C, respectively	41
3.8	Room temperature PL characterization of ZnO thin film deposited at RT	42
3.9	(a) X-ray spectra of ZnO thin film deposited on n-Si, (b) Relationship between FWHM and peak position and (c) Lattice constant and bi axial stress analysis with various Ar/O ₂ gas flow rates (50/0, 35.5/5 and 28/11.5 sccm) at room temperature deposition	43

3.10	(a) X-ray spectra of ZnO thin film deposited on n-Si, (b) Relationship between FWHM and peak position and (c) Lattice constant and bi-axial stress analysis with various Ar/O ₂ gas flow rates (50/0, 35.5/5 and 28/11.5 sccm) at 300 °C substrate deposition	44
3.11	(a-c) AFM images of deposited nano-crystalline ZnO thin films at room temperature for Ar/O ₂ gas flow rates varying from 50/0, 35.5/5 and 28/11.5 sccm, respectively	45
3.12	(a-c) AFM images of ZnO thin films at 200 °C for Ar/O ₂ gas flow rates of 50/0, 35.5/5 and 28/11.5 sccm, respectively	46
3.13	(a-c) AFM images of ZnO thin films at 300 °C for Ar/O ₂ gas flow rates of 50/0, 35.5/5 and 28/11.5 sccm, respectively	46
3.14	Variation of RMS roughness of deposited ZnO thin films with different Ar/O ₂ gas flow rates at deposition temperature between RT to 300 °C	47
4.1	Schematic Diagram of Vapour-Liquid-Solid (VLS) Process from Initial Nucleation to Continuous Growth	50
4.2	Schematic diagram of VS process from initial nucleation to continuous growth	51
4.3	X-ray diffraction spectra of ZnO NRs on n-Si substrate with growth temperature varying from 500 °C to 600 °C	53
4.4	FESEM images with (a), (c) Top View and (b), (d) Cross-Sectional View of ZnO NRs with substrate temperature varying from 500 °C to 600 °C	54
4.5	AFM images with (a), (c) 2-D View and (b), (d) 3-D View of ZnO NRs with substrate temperature varying from 500 °C to 600 °C	54
4.6	Raman spectra of ZnO NRs deposited at substrate temperature of 500 °C and 600 °C	55
4.7	X-Ray Diffraction Spectra for ZnO Nanorods Grown over Substrates - (a) Pt-Si (111), (b) ITO Coated Glass, (c) Ge, (d) n-Si (100) and (e) Polyimide, respectively	57
4.8	Top View FESEM Images of ZnO NRs Grown over (a) n-Si, (b) Ge, (c) ITO Coated Glass, (d) Pt-Si (111) and (e) Polyimide Substrate, respectively	58
5.1	FESEM Images of ZnO NRs: (a) Top view, (b) 45° Tilted view and (c) Cross-sectional view	62
5.2	(a) 2-D and (b) 3-D View AFM Images of the ZnO NRs	63
5.3	(a) XRD 2θ-ω Scan, (b) Variation of $(K*hv)^2$ with photon energy (hv), and (c) Raman spectra of ZnO NRs Deposited on n-Si (100) Substrate, respectively	64
5.4	(a) Schematic of the device structure, and (b) I-V Characteristics of Al/Si/Al and Al/ZnO/Al contacts	64
5.5	Energy band diagram of ZnO/n-Si heterojunction (HJ) (a) Before and (b) After thermal equilibrium	65
5.6	(a) Room temperature I-V characteristics of ZnO NRs/Si HJ and (b) Current conduction mechanism in forward bias I-V plot of ZnO NRs/Si HJ	66
5.7	Forward bias temperature dependent I-V characteristics in temperature range varying from 120-300 K with incremental steps of 30K	67
5.8	Schottky barrier height and ideality factor varying with operating temperature	68
5.9	Temperature dependent Richardson plot of $\ln(I_0/T^2)$ versus q/kT for 120-300K operating temperature range	69
5.10	Plot of effective barrier height versus q/kT	70
5.11	Modified Richardson plot of $\ln\left(\frac{I_0}{T^2}\right) - \left(\frac{q^2 \sigma^2}{2k^2 T^2}\right)$ versus $q/2k$	71
5.12	(a) Top view (b) Cross-sectional view of FESEM images of ZnO NRs, (c) TEM image and (d) SAED Pattern of ZnO NR	73
5.13	(a) X-Ray Diffraction 2θ- ω Scan, (b) Room Temperature PL Spectra	74
5.14	Magnetization versus Magnetic Field (M-H) Curve for (a) ZnO NRs /Si and bare Si, and (b) ZnO NRs	74
5.15	(a) The schematic diagram of ZnO NRs/n-Si single heterojunction (SHJ) and ZnO NRs/n-Si/ZnO NRs double heterojunctions (DHJs), (b) Schematic of energy band diagram for ZnO NRs/n-Si/ZnO NRs DHJs	75
5.16	(a) Room temperature J-V characterization for ZnO NRs/Si SHJ and ZnO NRs/Si/ZnO NRs DHJs, (b)-(c) Linear fitting of forward bias region for SHJs and DHJs, respectively and (d) Extraction of Schottky barrier height of reverse bias of SHJs	77
5.17	(a) Resistivity response of ZnO NRs/Si/ZnO NRs device at 70°C for pure hydrogen and (b), (c) Exponential fitting of resistivity response curve for recovery and response time, respectively	78

5.18	Schematic diagram of gas sensing mechanism of ZnO NRs: (a) lesser number of defects, (b) ZnO NRs with defects at low temperature (<150 °C) and (c) ZnO NRs with defects at High (>150 °C) Operating Temperatures, respectively	80
6.1	(a) Top view, (b) Tilted view (17° off normal), (c) Cross sectional View (87° off normal) of FESEM images and (d) AFM 2D image of ZnO NRs	85
6.2	2θ-ω scan of X-Ray diffraction pattern of ZnO NRs	85
6.3	Room Temperature CL Spectra of ZnO NRs	86
6.4	(a) Schematic diagram of nanosensor, (b) I-V Characteristics of nanosensor at 75 °C without and with 1% and 5% H ₂ concentration	87
6.5	Resistance response curve with time at 100 °C for (a) 1% and (b) 5% H ₂ Concentration	87
6.6	Temperature Dependent Resistive Response Curve: (a) 1% Hydrogen and (b) 5% Hydrogen in argon	88
6.7	(a- d) Resistive response curve with recovery and response time exponential fitting for 1% H ₂ and 5% H ₂ concentration at 100 °C, respectively	89
6.8	(a) Response Time, (b) Recovery time of nano- sensors in presence of 1% and 5% hydrogen with change in temperature varies from 50 °C to 150 °C	90
6.9	Sensor's relative response versus temperature curve for varying hydrogen concentration	91
6.10	(a), (b) Proposed gas sensing mechanism and (c), (d) Forward and reverse bias energy band diagram at Schottky junction	91
6.11	Relative response curve with time for various hydrogen concentration ranging from 7 ppm to 1% (in Pure Argon) with increasing operating temperature from 50 °C to 175 °C	93
6.12	Sensors relative response with operating temperature ranging from 50 °C to 175 °C for 7 ppm to 1% hydrogen concentrations	93
6.13	(a) Response Time, and (b) Recovery Time for various hydrogen concentration ranging from 7ppm to 1% at 100 °c and 150 °c, respectively	94
6.14	(a-c) Relative response curve with time and (d-f) Sensors response with operating temperature variation for CH ₄ , H ₂ S and CO ₂ gases for various gases concentration while operating temperature varies from 100 °C to 175 °C	95
6.15	Selectivity properties of Pd/ZnO NRs based sensors for CH ₄ , H ₂ S, CO ₂ , H ₂ Gases, at concentration of 7 ppm to 10,000 ppm (1%), respectively at 175 °C operating temperature	96
7.1	(a) Cross Sectional View, (b) Top View of FESEM Images of un-irradiated ZnO NRs	101
7.2	2D AFM Images of (a) Un-Irradiated and gamma-irradiated ZnO NRs with irradiation doses of (b) 1 kGy, (c) 2 kGy, (d) 5 kGy, (e) 8 kGy and (f) 10 kGy, respectively	101
7.3	(a), (b), (c), (d) and (e) X-Ray Diffraction (XRD) Patterns of Un-Irradiated and Gamma-Irradiated ZnO NRs with Irradiation Doses of 1 kGy, 2 kGy, 5 kGy, and 10 kGy, respectively	102
7.4	Room temperature PL spectra of un-Irradiated and gamma irradiated ZnO NRs with 10 kGy dose	103
7.5	Resistive response curve of un-irradiated and gamma irradiated ZnO NRs based sensors with irradiation doses of 1 kGy, 2 kGy, 5 kGy and 10 kGy at 150 °C operating temperature: (a) 1% and (b) 5% hydrogen concentration in pure argon	103
7.6	(a) Response Time and (b) Recovery Time for un-irradiated and gamma irradiated ZnO NRs based sensors with irradiation doses of 1 kGy, 2 kGy, 5 kGy and 10 kGy at 150 °C operating temperature at H ₂ concentrations of 1% and 5%	104
7.7	Relative response of ZnO NRs based hydrogen sensor as a function of un-irradiated and gamma irradiated for various irradiation doses for: (a) 1% and (b) 5% H ₂ concentration	105
7.8	Schematic diagram of hydrogen gas sensing mechanism of un-irradiated ZnO NRs: (a) In air, (b) In hydrogen, (c) Effect of low gamma dose and (d) Effect of high gamma dose	106
8.1	2θ-ω Scan of XRD Spectra of nano crystalline ZnO thin films: (a) un-Irradiated (Pristine), and irradiated at ion fluences of (b) 1×10 ¹¹ ions/cm ² , (c) 1×10 ¹² ions/cm ² and (d) 1×10 ¹³ ions/cm ²	111
8.2	Variation of FWHM with ion fluence at increasing rate from 1×10 ¹¹ ions/cm ² to 1×10 ¹³ ions/cm ²	112
8.3	Variation of compressive stress with ion fluences at increasing rate from 1×10 ¹¹ ions/cm ² to 1×10 ¹³ ions/cm ²	113
8.4	Normalized CL spectra of pristine and irradiated ZnO thin films at room temperature	113

8.5	AFM 2-D images of ZnO thin films: (a) Pristine (un-Irradiated), irradiated at (b) 1×10^{11} ions/cm ² , (c) 1×10^{12} ions/cm ² , (d) 1×10^{13} ions/cm ² fluences of Au ions, respectively	114
8.6	Top View SEM images for (a) Pristine and (b) 1×10^{13} ions/cm ² Au SHI irradiated ZnO thin film	115
8.7	(a) 2D PSD Plot v/s Spatial Frequency and (b) RMS Roughness and Fractal Dimension variation at different ion fluences, respectively	115
8.8	Temperature dependent resistive response curve for 5% hydrogen concentration on (a) Pristine, and irradiated ZnO thin film with 120 MeV Au at ion fluences of (b) 1×10^{11} ions/cm ² , (c) 1×10^{12} ions/cm ² and (d) 1×10^{13} ions/cm ² , Respectively	117
8.9	Relative response variation of ZnO thin film sensor with various ion fluences for 75 °C to 175°C operating temperature	118