

## List of Figures

Figures	Title	page
1.1	World energy demand by energy source	1
1.2	(a) Power generation by various energy source and (b) Growth of renewable energy sources from 2012 to 2040	2
1.3	Schematic illustration of the developing metal oxide with new properties to enhance its application in various fields	3
2.1	Plot of compiled values of highest confirmed photo conversion efficiencies for research cells for various photovoltaic technologies from 1976 to the present. This plot is courtesy of the National Renewable Energy Laboratory, Golden, CO.	6
2.2	Price range for residential applications in different countries for installed PV systems	7
2.3	Schematic illustration of (a) DSSC and (b) charge transport in the cell	9
2.4	Schematic representing the mechanism of photodegradation under sunlight	13
3.1	Schematic illustration of nano-TiO <sub>2</sub> synthesis using reactor at temperatures ranging from -40°C to -10°C	20
3.2	Schematic illustration of TiO <sub>2</sub> synthesis process	21
3.3	XRD pattern of nano-TiO <sub>2</sub> synthesized at -40°C to -10°C where planes at (101) and (110) represents anatase and rutile phase respectively	21
3.4	Raman analysis of nano-TiO <sub>2</sub> synthesized at -40 °C to -10 °C	22
3.5	(a) to (d) Williamson–Hall plot of nano-TiO <sub>2</sub> synthesized at -40°C to -10°C respectively	23
3.6	(a) to (d) TEM and HRTEM showing nano-TiO <sub>2</sub> synthesized at -40°C to -10°C respectively	25
3.7	(a) and (b) TEM images, (c) and (d) HRTEM images with marked inter planar distance and (e) and (f) are SAED pattern of -40 °C and -10 °C respectively. Dotted lines in (e) and (f) are guide to eye	25
3.8	N <sub>2</sub> -adsorption–desorption isotherms of nano-TiO <sub>2</sub> prepared at -40 °C and -10°C	26
3.9	(a) to (d) hv and (hvF(R <sub>∞</sub> )) <sup>(1/2)</sup> plot of nano-TiO <sub>2</sub> synthesized at -40°C to -10°C respectively	26
3.10	XRD patterns of the TiO <sub>2</sub> doped with ZnO of varying weight percentage (0, 1, 5 and 10%). The inset on right side shows the respective (101) peak used for fitting and particle size calculation	28
3.11	(a) Full range XPS survey spectra, high resolution spectra of (b) Zn 2p, (c) Ti 2p and (d) O 1s of TiO <sub>2</sub> solid nanospheres with different ZnO doping	29
3.12	(a-d) FESEM images and (e-h) TEM images of TiO <sub>2</sub> solid nanosphere doped with ZnO of 0, 1, 5 and 10% by weight respectively	30
3.13	(a) TEM image, (b) HRTEM image and (c) ED pattern of TiO <sub>2</sub> solid nanosphere with 5% ZnO doping. (d-f) EDS maps of Ti K (red), Zn K (yellow) and O K (green). (g) Bar graph displaying atomic % obtained from EDS spectra by varying the ZnO doping levels	30
3.14	(a) N <sub>2</sub> adsorption-desorption BET isotherm of TiO <sub>2</sub> solid nanospheres with different ZnO doping. (b) Effect of varying ZnO doping level on surface area and average pore size	31
3.15	Schematic demonstrating the synthesis method for hydrogenated TiO <sub>2</sub> nanospheres doped with HfO <sub>2</sub> nanodots	32
3.16	FESEM images of (a) TiO <sub>2</sub> (b) 1% doped HfO <sub>2</sub> /TiO <sub>2</sub> (c) 1% doped H-HfO <sub>2</sub> /TiO <sub>2</sub> (d) 5% doped HfO <sub>2</sub> /TiO <sub>2</sub> and (e) 10% doped HfO <sub>2</sub> /TiO <sub>2</sub>	33
3.17	(a) TEM images of H-HfO <sub>2</sub> /TiO <sub>2</sub> and (b) a highly magnified view of H-HfO <sub>2</sub> /TiO <sub>2</sub> nanosphere (c) High resolution TEM image and (d) SAED pattern of H-HfO <sub>2</sub> /TiO <sub>2</sub> (e) EDS spectrum and (f-h) EDS maps corresponding to Hf M, Ti K and O K signal respectively. Note that the signal C K in e originates from the carbon tape and can be neglected.	34
3.18	XRD patterns of (a) hydrogenated HfO <sub>2</sub> /TiO <sub>2</sub> and TiO <sub>2</sub> and (b) HfO <sub>2</sub> /TiO <sub>2</sub> and TiO <sub>2</sub> without hydrogenation	34
3.19	(a) Schematic demonstrating the light interaction with HfO <sub>2</sub> doped hydrogenated TiO <sub>2</sub> nanosphere. (b) UV-vis diffuse reflectance spectra and (c) Tauc plot of (ahv) <sup>1/2</sup> versus energy for band gap calculation of TiO <sub>2</sub> , HfO <sub>2</sub> /TiO <sub>2</sub> and H-HfO <sub>2</sub> /TiO <sub>2</sub> (d) (ahv) <sup>1/2</sup> versus energy and reflectance spectra (inset) for H-TiO <sub>2</sub> and H-HfO <sub>2</sub> /TiO <sub>2</sub>	34
3.20	Raman spectra of H-HfO <sub>2</sub> /TiO <sub>2</sub> and H-TiO <sub>2</sub>	35
4.1	Schematic illustration of nano-TiO <sub>2</sub> synthesis using reactor at temperatures ranging from -40°C to -10°C	37
4.2	(a) Bargraph shows the composition of S1, S2 and S3. (b) Cross sectional image of film S1	38

and inset SEM image show uniformly oriented nanoparticles with high porosity (c) and (d) Diffuse reflectance spectra of S1, S2 and S3 photoanodes before and after dye loading respectively

4.3	AFM images of the S1, S2 and S3 sample photoanodes	39
4.4	Dye absorbed amount of S1, S2 and S3 sample photoanodes are calculated using absorption spectra	40
4.5	Schematic showing film structures and their respective light scattering	41
4.6	(a) Schematic representation of fabricated DSSC (b) Current density – voltage curves of the DSSC consisting -40 °C, -10 °C, P25, S1, S2 and S3 samples as photoanodes under one sun illumination	42
4.7	Nyquist plot of DSSC with S1, S2 and S3 samples as photoanodes (a) under illumination and (b) in dark respectively	42
4.8	UV-vis diffuse reflectance spectra of TiO <sub>2</sub> solid nanospheres with various ZnO %	43
4.9	(a) J-V characteristics of DSSC with photoanode based on TiO <sub>2</sub> solid nanospheres with different ZnO doping (b) Bar graph displaying photovoltaic parameters obtained for different DSSC devices fabricated by varying the ZnO doping levels	44
4.10	(a) J-V characteristics and (b) Nyquist plot with equivalent circuit (inset) of ZnO-TiO <sub>2</sub> solid nanospheres with 2% and 3% ZnO as photoanode in DSSC	45
4.11	Absorbance spectra of the TiO <sub>2</sub> solid nanospheres with various ZnO %. Amount of dye absorbed amount is calculated using Beers Lambert law	45
4.12	Nyquist plot and equivalent circuit (inset) of ZnO-TiO <sub>2</sub> solid nanosphere with various ZnO % as photoanode in DSSC	46
4.13	Energy level diagram for working electrode of DSSCs based on TiO <sub>2</sub> solid nanosphere with various ZnO %	47
4.14	(a) Cross-sectional SEM image of the photoanode deposited on FTO along with its magnified image. Note that Au/Pd metal layer is sputtered on photoanode for improving the image contrast and (b) A schematic showing sandwich model of the fabricated DSSC device	48
4.15	(a) Current density and voltage characteristics of the DSSC fabricated in this study and (b) Nitrogen adsorption-desorption isotherms of H-HfO <sub>2</sub> /TiO <sub>2</sub> and H-TiO <sub>2</sub> . The isotherm can be classified as type-IV with a hysteresis loop. The surface area of H-HfO <sub>2</sub> /TiO <sub>2</sub> is (74.21m <sup>2</sup> /g) more as compared to H-TiO <sub>2</sub> (56.186 m <sup>2</sup> /g)	48
4.16	Absorbance spectra of the dye deloaded from H-HfO <sub>2</sub> /TiO <sub>2</sub> and H-TiO <sub>2</sub> photoanode	49
4.17	(a) Nyquist plot and (b) Bode plot for the DSSC based on H-HfO <sub>2</sub> /TiO <sub>2</sub> and H-TiO <sub>2</sub> . Inset of (a) is the equivalent circuit diagram used for fitting the curves	50
5.1	Schematic illustration of (a) drop casting, (b) spin coating and (c) screen printing techniques	52
5.2	XRD pattern of graphite, graphene oxide and graphene	53
5.3	(a) Raman analysis of graphene and (b) FTIR analysis of graphene oxide and graphene	54
5.4	SEM images of (a) graphite, (b) graphene oxide, (c) graphene and (d) TEM image of graphene	54
5.5	XRD patterns of film surface fabricated at various temp. by (a) drop casting, (b) spin coating and (c) screen printing respectively. Dotted line is a eye guide to understand graphene peak	55
5.6	SEM images of film surface fabricated by (a) drop casting, (b) spin coating and (c) screen printing respectively	56
5.7	(a) Photograph of graphene counter electrode DSSC with its schematic representation (b) current density-voltage curve and (c) Impedance study of all DSSCs	56
5.8	Photograph of SS-catalyst counter electrode DSSC and inset shows a schematic illustration of DSSC where carbon materials are graphite, graphene and MWCNT	58
5.9	Shows the SEM photographs of the SS coated with (a) graphite, (b) graphene, (c) MWCNT and (d) Pt	59
5.10	Relation between the (a) R <sub>sh</sub> of various SS-substrates and fill factor, and (b) with DSSC efficiency	59
5.11	Shows the SEM photographs of the SS coated with (a) graphite, (b) graphene, (c) MWCNT and (d) Pt.	60
5.12	Current density – voltage curves of the DSSC consisting -40 °C and -10 °C samples as photoanodes with (a) 0.09 and (b) 0.04 cm <sup>2</sup> active area respectively, under one sun illumination	61
5.13	Nyquist plot of -40 °C and -10 °C samples DSSC with (a) 0.09 and (b) 0.04 cm <sup>2</sup> active area	62

	respectively	
5.14	Current density – voltage curves of the DSSC consisting -40 °C and -10 °C samples as photoanodes with (a) Pt and (b) graphene counter electrode with 0.04 cm <sup>2</sup> active area	63
5.15	Current density – voltage curves of the DSSC consisting (a) 1% ZnO-TiO <sub>2</sub> and (b) H-HfO <sub>2</sub> /TiO <sub>2</sub> samples as photoanodes with graphene counter electrode with 0.04 cm <sup>2</sup> active area	63
6.1	World energy demand by energy source	65
6.2	Schematic illustration of photocatalytic membrane fabrication	66
6.3	SEM images of blank and TiO <sub>2</sub> coated filter paper/membrane and inset shows cross-sectional SEM images of TiO <sub>2</sub> coated filter membrane	67
6.4	Photographic stepwise illustration of photo-catalytic membrane restored using 1 sun radiation	67
6.5	HRTEM images of sub-zero temperature synthesized at -10 and -40°C	68
6.6	Comparison of (a) photocatalytic activities and (b) rate constant of sub-zero temperature (-40 to -10°C) photo-catalytic membrane	68
6.7	Schematic illustration of ZnO-TiO <sub>2</sub> heterojunction solid nanospheres morphology	69
6.8	Comparison of (a) photocatalytic activities and (b) photoreduction up to four cycles of 0 to 10% ZnO-TiO <sub>2</sub> photo-catalytic membrane	69
6.9	Schematic illustration of the band gap engineering of TiO <sub>2</sub> nanospheres by hydrogenation and doping with HfO <sub>2</sub> nanodots	70
6.10	(a) – (b), (c) – (d), (e) – (f) and (g) – (h) are photocatalytic activities – reaction of TiO <sub>2</sub> , H-TiO <sub>2</sub> , HfO <sub>2</sub> /TiO <sub>2</sub> and H-HfO <sub>2</sub> /TiO <sub>2</sub> respectively, and left portion of figure shows chemical structure of all dyes	71
6.11	Comparison of (a) photocatalytic activities and (b) rate constant of hydrogenated TiO <sub>2</sub> and HfO <sub>2</sub> /TiO <sub>2</sub>	72

