

List of Figures

Figures	Title	page
1.1	Areas of application for MW absorbing materials (a) Stealth materials for RCS reduction of airborne application (Source: Vinoy and Jha, 1996) (b) Attenuation of EM pollution (c) MW radiation shielding in house hold devices (d) Suppression of EM radiation during MW measurements (Source: Comsol)	3
2.1	Interaction of EM wave with matter	7
2.2	Microwave interaction with different mediums (Source: Sutton, 1989)	8
2.3	Reflection mechanism of MW signals from metallic and non-metallic surfaces	9
2.4	Interaction of MW signals with MW absorbing Materials (Source: Hernandez <i>et al.</i>)	9
2.5	Dielectric relaxation mechanism with incident EM radiation	10
2.6	Spin resonance relaxation mechanism (a) Precession under the influence of external magnetic field (b) Dissipation of EM signal	11
2.7	Interaction of MW with single layer absorber with conducting backing	12
2.8	Scheme for Salisbury Screen (Source: Vinoy and Jha, 1996)	17
2.9	Scheme for Jaumann absorber (Source: Vinoy and Jha, 1996)	18
2.10	Foam based broad band MW absorbers (Source: Vinoy and Jha, 1996)	18
2.11	(a) Scheme for circuit analog RAM and its equivalent circuit elements (b) some standard circuit analog geometries in form of rectangular slots, dipoles, Jerusalem crosses etc. (Source: Vinoy and Jha, 1996)	19
3.1	Process flow chart for gel to carbonate precipitation route followed by sequential annealing	30
3.2	Process flow chart for synthesis of graphite coated core-shell metal nanoparticles	31
3.3	Process flow chart for sol-gel synthesis route	32
3.4	Process flow chart for solid state synthesis of ferroelectric ceramics	33
3.5	(a) Two roll mixing mill (b) Pressing of rubber sheets using high temperature compression moulding press, mold for pressing and fabricated flexible rubber sheet	34
3.6	(a) Schematic for of geometrical arrangement of X-ray diffractometer (Source: Cullity, 1956) (b) PANalytical X'pert Pro diffractometer instrument used for XRD studies	35
3.7	(a) Schematic for optical design of FTIR spectrometer (b) Bruker FTIR spectrometer Vertex 70v used for IR studies	36
3.8	(a) Schematic for design of vibrating sample magnetometer (source: Foner, 1959) (b) ADE vibrating sample magnetometer EV5 used in M-H studies	37
3.9	(a) Schematic for optical design of Raman Microscope (Source: Schrader, 1995) (b) Nomadic Raman spectrophotometer (Make: BaySpec, USA) used for studies	37
3.10	(a) Schematic block diagram of scanning electron microscope (SEM) (Source: Purdue University) (b) Carl Zeiss EVO 18 scanning electron microscope in conjunction with EDS assembly for morphological and elemental analysis	38
3.11	(a) Schematic block diagram of transmission electron microscope (TEM) used in imaging and diffraction mode (Source: Williams and Carter, 2009) (b) FEI Technai G2 model of Transmission Electron Microscope used for characterization	39
3.12	(a) Schematic block diagram of SQUID magnetometer (Black <i>et al.</i> , 2006; WMI, Germany, 2015) (b) Quantum Design SQUID magnetometer MPMS Evercool used for measurement	40
3.13	(a) Schematic block diagram of particle size analyzer (b) Microtrac (S3500) particle size analyzer used for analysis	41
3.14	Depiction of S-parameters in two port transmission line measurement system	41
3.15	(a) Block diagram of Vector Network Analyzer (b) Rohde & Schwarz ZVM VNA system used for MW characterization	42
3.16	a) Rectangular wave guide fixture (b) Co-axial wave guide fixture (c) Rectangular sample holders for R, S, G, J, X and Ku bands (d) Co-axial sample holder	43
4.1	Crystal structure of spinel ferrite system	45
4.2	Depiction of interionic bond length and bending angle in different configuration of spinel structures (Source: Smit and Wijn 1959)	46
4.3	XRD pattern of ferrite compositions annealed at different elevated temperatures of 650°C, 950°C and 1250°C (a) NiFe ₂ O ₄ (b) Ni _{0.75} Zn _{0.25} Fe ₂ O ₄ (c) Ni _{0.5} Zn _{0.5} Fe ₂ O ₄ (d) Ni _{0.75} Zn _{0.25} Fe ₂ O ₄	49

4.4	(a) XRD pattern of different ferrite compositions annealed at 1250°C (b) Shift of XRD peak corresponding to (331) plane with Zn ²⁺ ion concentration (c) Change in lattice parameters with fraction of Zn ²⁺ ion content	49
4.5	(a) FTIR pattern of Ni _{0.5} Zn _{0.5} Fe ₂ O ₄ ferrite powders annealed at elevated temperatures of 650°C, 950°C and 1250°C (b) Variation in FTIR spectra for Ni _{1-x} Zn _x Fe ₂ O ₄ ferrite powder with Zn ²⁺ ion concentration (x=0, 0.25, 0.5 and 0.75)	50
4.6	SEM micrograph of Ni _{1-x} Zn _x Fe ₂ O ₄ powder annealed at elevated temperatures of 650°C, 950°C and 1250°C for (a) x=0 (b) x=0.5	51
4.7	EDS spectra of Ni _{1-x} Zn _x Fe ₂ O ₄ powder annealed at elevated temperatures of 1250°C for (a) x=0 (b) x=0.5	52
4.8	Room-temperature M-H Hysteresis curves of Ni _{1-x} Zn _x Fe ₂ O ₄ ferrite powders at (a) x=0 (b) x=0.25 (c) x=0.50 (d) x=0.75	53
4.9	Variation of saturation magnetization (M _s) & coercive field (H _c) with annealing temperature (b) Variation of M _s & H _c with fraction of Zn ²⁺ ion content	53
4.10	Frequency dependence of the relative complex permeability for annealed Ni _{1-x} Zn _x Fe ₂ O ₄ powder (a) x=0 (b) x=0.25 (c) x=0.50 (d) x=0.75	55
4.11	Frequency dependence of the loss tangent (tanδ _m) for annealed Ni _{1-x} Zn _x Fe ₂ O ₄ powder (a) x=0 (b) x=0.25 (c) x=0.50 (d) x=0.75 (e) Variation of maximum loss tangent with Zn concentration at resonating frequency of 6 GHz	56
4.12	(a) Real permittivity plots for ferrite loaded rubber composites FMAR50-80 with MW frequencies (b) Real permeability behavior of ferrite loaded rubber composites (c) Imaginary permeability plots of ferrite loaded rubber composites (d) Loss tangent profiles for ferrite loaded rubber composites	57
4.13	Optimal Reflection Loss (R.L.) over frequency range 2-12.4 GHz and matching thicknesses of ferrite loaded rubber composites (a) FMAR50 (b) FMAR60 (c) FMAR70 (d) FMAR80 (e) variation of maximum reflection loss with ferrite powder loading fraction in composite (f) optimal R.L. bandwidth profile with composite absorber thickness	58
5.1	Origin of interfacial polarization in core-shell structures	62
5.2	Schematic for formation of graphite coated core-shell structure	63
5.3	XRD pattern of samples N ₁ , N ₂ , N ₃ and N ₄	64
5.4	FTIR pattern of samples N ₁ , N ₂ , N ₃ and N ₄	64
5.5	TEM micrograph for (a) Sample N ₁ (b) N ₂ (c) N ₃ (d) N ₄	65
5.6	(a) HRTEM micrograph for sample N ₄ (b) SAED pattern of Ni core (c) SAED pattern of graphitic shell	66
5.7	Raman spectra for sample N ₃ and N ₄	67
5.8	M-H hysteresis curves at different temperatures for graphite coated Ni nanomaterial samples (a) N ₂ (b) N ₃ (c) N ₄ (d) Variation of coercive field H _c with cooling down of samples during magnetic measurements and variation of saturation magnetization in sample N ₂ -N ₄	67
5.9	ZFC and FC magnetization curves for sample (a) N ₂ (b) N ₃ (c) N ₄ in the temperature range 5-300K at applied magnetic field of 500 Oe	68
5.10	Frequency dependent plots of different filler loaded rubber composites for (a) Real relative permittivity ε _r ' (b) Imaginary relative permittivity ε _r '' (c) dielectric loss tangent tanδ _e (d) Variation of maximum loss tangent (tanδ _e) _{max} with filler loading fraction of N ₄ powder	69
5.11	Optimal Reflection Loss (R.L.) over frequency range 12.4-18 GHz and matching thicknesses of N ₄ powder loaded rubber composites (a) NIBR40 (b) NIBR50 (c) NIBR60 (d) NIBR70 (e) NIBR75 (f) variation of maximum reflection loss with functional filler loading fraction in composites	71
6.1	(a) Crystal structure of tetragonal BaTiO ₃ , (b)-(c) Polarization in BaTiO ₃ due to displacement of Ti ⁴⁺ ions	74
6.2	(a) Schematic for solid state synthesis of tetragonal BaTiO ₃ powder and fabrication of rubber based composites	75
6.3	(a) XRD pattern of BaTiO ₃ powder samples annealed at different elevated temperatures of 700°C, 900°C, 1000°C, and 1100°C (b) variation of tetragonality ratio with annealing temperature	76
6.4	FTIR pattern of BaTiO ₃ powder samples annealed at different elevated temperatures of 700°C, 900°C, and 1100°C	77
6.5	Raman pattern of BaTiO ₃ powder samples annealed at different elevated temperatures of 700°C, 900°C, 1000°C, and 1100°C	77

6.6	SEM micrographs of BaTiO ₃ powder samples annealed at different elevated temperatures of 700°C, 900°C, 1000°C, and 1100°C (b) Representative EDX spectra for BaTiO ₃ powder sample annealed at 1100°C	78
6.7	(a) Real and imaginary permittivity plots for annealed BaTiO ₃ powders over 8-18 GHz frequency range (b) Dielectric loss tangent (tanδ _e) plots for respective powder samples	79
6.8	(a) Real and (b) Imaginary permittivity of BaTiO ₃ /NBR composite with different loading of BaTiO ₃ powder annealed at 1100°C	80
6.9	Calculated R.L. plots for BaTiO ₃ /NBR composites over 8-18 GHz for (a) Pure NBR sheet (b) Pure BaTiO ₃ powder sample and BaTiO ₃ powder rubber composite samples with filler loading of (c) 50 wt% (d) 60 wt% (e) 70 wt% (f) 80 wt%	81
6.10	Thickness dependent reflection loss profile for 80 wt% loaded rubber composite (b) Schematic for possible microwave absorption in rubber composites	82
6.11	R3c crystal arrangement of BFO multiferroics [Source: Shima <i>et al.</i> , 2013]	83
6.12	Process flow chart for synthesis of BFO nanocrystalline powder	84
6.13	XRD spectra of BFO powders sample annealed at 350°C (2h) and 600°C (4h)	85
6.14	FTIR spectra of BFO post annealed powder sample at 600°C for 4h	85
6.15	SEM micrograph for (a) 350°C annealed sample (b) Post annealed sample at 600°C for 4h (c) Corresponding EDX spectra	86
6.16	Room temperature M-H curves for BFO sample annealed at 600°C for 4h duration	87
6.17	(a) Complex permittivity plots for 600°C annealed BFO powders over 8-18 GHz frequency range (b) Dielectric loss tangent (tanδ _e) plot for respective powder sample (c) Real permittivity plots for BFO powder loaded rubber composites (d) Imaginary permittivity plots for respective rubber composites	87
6.18	Calculated R.L. plots for BFO/NBR composites over 8-18 GHz for rubber composite samples with filler loading of (a) 50 wt% (b) 60 wt% (c) 70 wt% (d) 80 wt%	88
6.19	Thickness dependent R.L. profile for BFR80 rubber composite	89
7.1	(a) Hexagonal lattice cell (b) Part of the phase diagram BaO-MeO-Fe ₂ O ₃ , where Me is divalent metal ion of Mn, Fe, Co, Ni, Zn or Mg etc. [Source: Pullar, 2012]	91
7.2	Crystal Structure of Z-type Hexaferrites (Sr ₃ Co ₂ Fe ₂₄ O ₄₁) (Source: Scott, 2013)	92
7.3	C-planer anisotropy in Sr ₃ Co ₂ Z hexaferrite	93
7.4	Process flow chart for synthesis of microwave absorbing Z-type hexaferrite powder	95
7.5	Process flow chart for fabrication of microwave absorbing ferrite tiles	96
7.6	Typical sintering cycle for treatment of ferrite tiles	96
7.7	Annealing temperature profile and corresponding X-ray diffraction patterns for different M, Z, and W phase hexaferrite powders	97
7.8	SEM micrographs for Sr ₃ Co ₂ Z hexaferrite powder annealed at 1250°C for different magnifications	98
7.9	Particle size distribution for Sr ₃ Co ₂ Z hexaferrite powder annealed at 1250°C	98
7.10	Room temperature M-H hysteresis curves for Sr ₃ Co ₂ Z hexaferrite powder annealed at (a) 950°C (b) 1250°C (c) 1350°C, and (d) Variation of saturation magnetization with annealing temperature	99
7.11	Frequency dependence of (a) Real permittivity (ε _r ') (b) Real permeability (μ _r ') (c) Imaginary permeability (μ _r '') (d) Loss tangent (tanδ _m) for hexaferrite powder samples annealed at 950°C, 1250°C, and 1350°C	100
7.12	Frequency dependence of (a) Real permittivity (ε _r ') (b) Real permeability (μ _r ') (c) Imaginary permeability (μ _r '') (d) Loss tangent (tanδ _m) for Z-type hexaferrite powder loaded rubber samples ZSR50-ZSR80	101
7.13	Optimal Reflection Loss (R.L.) over frequency range 8-18 GHz and matching thicknesses of ferrite loaded rubber composites (a) ZSR50 (b) ZSR60 (c) ZSR70 (d) ZSR80	102
7.14	(a) Thickness dependent (R.L.) values of Sr ₃ Co ₂ Z ferrite sintered tile (b) Variation of MW absorption bandwidth and maximum (R.L.) values with thickness of ferrite tile	103

List of Tables

<i>Table</i>	<i>Title</i>	<i>page</i>
2.1	Literature review for synthesis of MW absorbing Ni-Zn spinel ferrites and their composites	20
2.2	Literature review for synthetic route for pure Z-type Ba/Sr hexaferrite powders	22
2.3	Literature review for synthesis of MW absorbing core-shell nanomaterials and their composites	24
2.4	Literature review for synthesis of MW absorbing BaTiO ₃ and their composites	26
2.5	Literature review for synthesis of MW absorbing BiFeO ₃ and its composites	25
3.1	List of additives used in rubber processing	33
3.2	List of dimension of rectangular wave guide sample holders for different MW frequency bands	43
4.1	Variation in magnetic moment with distribution of cations in Ni-Zn ferrite system	47
4.2	Stoichiometric ratio of salt precursors for preparation of ferrite powders (50g batch size)	47
4.3	List of Ni _{0.5} Zn _{0.5} Fe ₂ O ₄ ferrite loaded rubber composites	48
4.4	Elemental analysis of NiFe ₂ O ₄ and Ni _{0.5} Zn _{0.5} Fe ₂ O ₄ ferrite compositions	51
5.1	List of sample N ₄ loaded rubber composites	63
5.2	Identified FTIR modes of vibration and corresponding wavenumber	65
6.1	List of tetragonal BaTiO ₃ powder loaded rubber composites	75
6.2	List of rubber composites loaded with BFO powder annealed at 600°C for 4h duration	84
7.1	List of Sr ₃ Co ₂ Z ferrite loaded rubber composites	94