

## List of Tables

<i>Table</i>	<i>Title</i>	<i>page</i>
2.1	Advantage and disadvantages of organic, inorganic and eutectic PCMs	13
2.2	Low temperature phase change materials with corresponding melting point and latent heat of fusion	14
2.3	High temperature phase change materials with corresponding melting point and latent heat of fusion	17
2.4	Methods used for thermal conductivity enhancement of PCMs and main outcomes	18
3.1	Advantage and disadvantages of DSC and T-history methods for PCMs	30
4.1	Comparison of T-history and DSC results for palmitic acid	41
5.1	The melting point, latent heat and molecular weight of pristine 1-dodecanol, lauric acid, myristic acid and palmitic acid PCMs	49
5.2	Comparison between computed and experimental results for DE-LA eutectic mixture	50
5.3	Comparison on computed and experimental results for DE-MA eutectic mixture	51
5.4	Comparison on computed and experimental results for DE-PA eutectic mixture	52
5.5	Thermal conductivity of 1-dodecanol, lauric acid, myristic acid, palmitic acid and eutectic compositions with respective standard deviation at room temperature (25 °C)	54
5.6	Melting point, latent heat of fusion and molecular weight of AM and BA substances	54
5.7	Melting point, latent heat of fusion and molecular weight of BA and PM system	55
6.1	Physical properties of test tubes, PCMs and DI water used for experiments	61
6.2	Melting and solidification temperatures of SAT and SAT+EG composite PCMs	65
8.1	Compositions of salt eutectics made from NaNO <sub>3</sub> , KNO <sub>3</sub> , LiNO <sub>3</sub> and NaCl	86
8.2	Melting point and latent heat of fusion of salt eutectics measured by DSC	89
8.3	Thermal conductivity of 88 wt% LiNO <sub>3</sub> – 11.2wt% NaCl/ ExG composites at different wt% of ExG and densities	90