List of Tables

Table	Title	Page
Table 2-1	: The five countries having rural population without the reach of clean water [Source: Water Aid,	2017]
		7
Table 2-2	2: Number of villages without sterile drinking water facility [Source : Kakoty, 2013]	9
Table 2-3	3: List of bacteria and their effects on health [Source : Boulos et al., 1999]	12
Table 3-1	: Technical parameters synchrotron-based micro-computed tomography technique (BL-4 Indus 2	,
	RRCAT Indore, India operating at 2.5 GeV, 200 mA.	29
Table 4-1	: Chemical composition of clay	38
Table 4-2	2: Chemical composition of organic filler	38
Table 4-3	3: Modelling of the fracture toughness (Y) using Eq. (H).	50
Table 5-1	: Chemical composition (Wt %) of porous ceramic adsorbent	57
Table 5-2	: Chemical composition (Wt %) of porous ceramic adsorbent	57
Table 5-3	3: The parameters obtained from fitting the sorption data of As (V) onto various porous ceramics	using
	pseudo-second order Eq. (Eq. 2). $h = kqe^2$ and R is the regression coefficient for the linear plot.	59
Table 5-4	: Transformation of As (V) in water [Source: Cheng et al., 2010]	61
Table 5-5	5: The parameters obtained from fitting the sorption data of As (V) onto various porous ceramics	using
	Freundlich Eq. (Eq. 5.4) and R is the regression coefficient for the linear plot.	64
Table 5-6	5: The parameters obtained from fitting the sorption data of As (V) onto various porous ceramics	using
	Langmuir Eq. (5.5) and R is the regression coefficient for the linear plot.	65
Table 5-7	7: E.coli removal data from FCC and CC ceramics	65
Table 6-1	: Chemical composition of the Marble additive and MCC ceramics	71
Table 6-2	2: The parameters obtained from fitting the sorption data of As (V) onto various porous ceramics	using
	pseudo-second order Eq. (Eq. 2). $h = kqe^2$ and R is the regression coefficient for the linear plot.	73
	: The parameters obtained from fitting the sorption data of As (V) onto various porous ceramics	
	Freundlich Eq. (6.2) and R is the regression coefficient for the linear plot.	76
	4: E.coli removal efficiency of MCC	78