

List of Figures

Figures	Title	Page
2.1	Schematic representation of (a) p-n junction solar cell (b) Band diagram of p-n junction under illumination.	5
2.2	(a) schematic representation for air mass ratio (AM) definition (b) Solar irradiance versus wavelength curve for AM ₀ , AM _{1.5G} and AM _{1.5D} solar spectra	6
2.3	Solar AM _{1.5G} spectrum and SQ limit of maximum efficiency of the single junction solar cell with respect to energy [Rühle, 2016]	6
2.4	One diode equivalent circuit for a solar cell in conjunction with series and shunt resistances.	7
2.5	Two diode equivalent circuit for solar cell	7
2.6	Phase diagram for CZTS taken from [Olekseyuk et al., 2004]	11
2.7	Representative defect levels in CZTS taken from reference [S. Chen, Walsh, Gong, & Wei, 2013]	12
2.8	Schematic representation of valance and conduction band offset at hetero interface	13
2.9	Schematic representation of type of band alignment at the hetero interface	14
2.10	Camera image of X-ray diffractometer at IIT Jodhpur	20
2.11	Camera image of (a) Scanning electron microscope and (b) DC sputter coating unit at IIT Jodhpur	21
2.12	Camera image of Atomic force microscope (AFM) system at IIT Jodhpur	21
2.13	Camera image of Cary 4000 UV- Vis spectrophotometer	22
2.14	Camera image of (a) Fourier transform infrared spectrometer and (b) Raman spectrometer unit at IIT Jodhpur	23
2.15	Camera image of (a) Semiconductor characterization system (SCS) and (b) Electrochemical workstation at IIT Jodhpur	23
3.1	(a) XRD micrograph of Mo deposited on SLG substrate (b) Surface and cross sectional image of Mo film deposited on SLG substrate	26
3.2	(a) Secondary electron microscopy (SEM) image and (b) Transmittance spectra of CBD deposited CdS thin film on glass substrate	27
3.3	Transmittance spectra of i-ZnO/Al:ZnO bilayer deposited on glass substrate with corrected transmittance of glass substrate	28
3.4	Schematic representation of complete device structure of CZTS solar cell	28
4.1	Schematic representation of process of formation of CZTS thin film	32
4.2	XRD micrographs of CZTS thin films at different processing temperatures (a) Chloride precursor route (MX) and (b) Nitrate precursor route (MXN)	33
4.3	(a) Texture coefficient, and (b) Grain size and dislocation density variation with processing temperature for MX and MXN CZTS thin films.	34
4.4	Room temperature Raman spectra of 300 °C annealed MX and MXN CZTS thin films.	35
4.5	Surface SEM micrograph and EDAX mapping (inset) for a) chloride precursor film b) nitrate precursor film and an schematic 3D representation of (c) chloride sol derived CZTS film, showing polycrystalline nature with large grains; (d) nitrate sol derived CZTS film, with blisters at the surface	36
4.6	EDAX compositional details for CZTS thin films prepared at different annealing temperature using (a) chloride sol (b) Nitrate sol	37
4.7	Cross-sectional SEM micrographs for 300 °C annealed (a) chloride sol derived (MX) (b) Nitrate sol derived (MXN) CZTS thin films and corresponding surface morphology (c) chloride sol derived (MX) (d) Nitrate sol derived (MXN)	37
4.8	($\alpha.E$) ² vs. photon energy plot for CZTS thin films processed at different annealing temperature using a) Chloride sol b) Nitrate sol	38
4.9	van der Paw resistivity mapping of CZTS thin film across 1 inch x 1 inch glass substrate prepared using a) Chloride sol and b) Nitrate sol after 300 °C annealing	39
4.10	Current-voltage characteristics of CZTS thin films prepared using (a) Chloride sol b) Nitrate sol at different temperature. Inset in both the graph represents room temperature resistivity of the films with processing temperature measured using van der Paw configuration	39
5.1	(a) Temperature profile used for final annealing of CZTS thin film under 5% H ₂ S+Ar gaseous	42

	environment (b) schematic representation of stacked multilayer (Al:ZnO/ZnO/CdS/CZTS/Mo/SLG) solar cell heterostructure with 3 mm x 3 mm area scribed for smaller solar cell structures	
5.2	XRD pattern of the post annealed CZTS thin films on (a) SLG substrate (CZTS/SLG), with reference kesterite CZTS phase (ICDD# 026-0575) (b) Mo/SLG substrate (CZTS/Mo/SLG)	42
5.3	Scanning electron micrograph of (a) CZTS thin film over Mo coated SLG substrate, (inset showing atomic fractions obtained through EDAX measurement); (b) cross sectional micrograph of stacked (AZO/ZnO/CdS/CZTS/Mo/SLG) device structure; (c) Cross sectional line scan showing elemental distribution across the layers; and (d) respective elemental distribution across the layers	43
5.4	$(\alpha.E)^2$ versus energy E (eV) curve for CZTS/SLG thin films with an arrow showing the extrapolated linear region of the curve	44
5.5	(a) Current density versus voltage (J - V) characteristics under dark and under 1 sun illumination conditions with inset showing device parameters (b) dark current-voltage characteristics for Al:ZnO/ZnO/CdS/CZTS/Mo/SLG solar cells and Open Circuit Voltage Decay analysis	45
5.6	(a) Open circuit voltage decay (OCVD) curve for the CZTS heterostructure device	46
5.7	Capacitance - voltage characteristics (a) and Mott-Schottky plots (b) for Al:ZnO/ZnO/CdS/CZTS/Mo/SLG solar cell, measured at different frequencies	46
5.8	(a) Impedance spectrograph for Al:ZnO/ZnO/CdS/CZTS/Mo/SLG solar cell with three different equivalent circuit models M ₁ , M ₂ and M ₃ , as explained in (a, b, c) and corresponding error in (d, e, f), where M ₃ corresponds to the best fit to the measured experimental impedance spectrograph.	48
5.9	Complex plane impedance plot in the dark under (a) forward bias and (b) reverse bias; (c) zoom view of the forward biased impedance plot, (d) resistance variation, (e) capacitance variation, and (f) minority carrier life times ($\tau_f=R_fC_f$ and $\tau_b=R_bC_b$) as a function of bias voltage for Al:ZnO/ ZnO/CdS/CZTS/Mo/SLG solar cells.	50
6.1	XRD patterns for sample S ₁ , S ₂ (Green color lines indicate the peak positions of CZTS according to ICDD # 26-0575).	55
6.2	SEM micrograph for (a) S ₁ and (b) S ₂ surfaces; and respective topographic images (c) S ₁ and (d) S ₂ samples	56
6.3	Tauc plot for CZTS thin film samples S ₁ and S ₂ ; used for estimating the band gap values	57
6.4	¹¹⁹ Sn Mossbauer spectroscopic measurements on S ₁ and S ₂ (a) CZTS samples, with standard Sn powder (b) as a reference.	57
6.5	Normalized temperature dependent resistance variation with temperature for (a) S ₁ and (b) S ₂ CZTS	58
6.6	Natural logarithm of conductivity against 1000/T plots for (a) S ₁ and (b) S ₂ CZTS samples, with inset showing the high temperature regions for respective samples	59
6.7	(a) Capacitance-Voltage (C-V) measurements (b) Mott-Schottky plots of photovoltaic devices based on S ₁ and S ₂ absorbers	60
6.8	(a) Photovoltaic characteristics of CZTS solar cell with S ₁ and S ₂ absorber in dark and under illumination (b) Dark IV characteristics of S ₁ and S ₂ solar cell	61
7.1	Schematic representation of multijunction solar cell	63
7.2	(a) Schematic representation of "Al:ZnO/ZnO/CdS/Absorber layer/Back contact" single junction solar cell structure, used for simulating the device performance and (b) the absorption coefficients of different materials used in the present work	64
7.3	(a) Band alignment at the interface and (b) Current-voltage (I-V) characteristics of single junction CZTS and CZTSe solar cells	66
7.4	(a) Open circuit voltage; (b) short circuit current density; (c) efficiency, and (d) quantum efficiency of CZTS and CZTSe absorber solar cells at different absorber layer thickness.	67
7.5	(a) Open circuit voltage; (b) short circuit current density; and (c) efficiency at different hole concentration for CZTS and CZTSe absorber based solar cells.	68
7.6	Impact of defect concentration (a) and absorber/CdS interface defect concentration (b) in efficiency for CZTS and CZTSe solar cells and contour plots showing variation of efficiency with minority carrier life time and interface recombination speed in CZTS (c); and CZTSe (d)	69
7.7	Impact of CdS buffer layer thickness and carrier concentration on CZTS (a) and CZTSe (b) solar cell efficiency	69
7.8	Conduction band offset (CBO) in (a) CZTS (b) CZTSe at different CdS layer electron affinity (χ_{CdS})	70

7.9	Impact of CdS electron affinity (band offset at absorber/CdS interface) on Voc (a); Jsc (b); and efficiency (c) for CZTS and CZTSe solar cells	71
7.10	Impact of interface recombination speed and CdS electron affinity on CZTS (a) Voc, (c) Jsc (e) efficiency and CZTSe (b)Voc (d) Jsc (f) efficiency	72
7.11	Impact of metal work function on Voc (inset Jsc) (a) and efficiency (b) for CZTS and CZTSe solar cell	72
7.12	Schematic representation of tandem cell structure with CZTS top cell and CZTSe bottom cell in conjunction with tandem connections	73
7.13	(a) Variation of current density of CZTS top cell and CZTSe bottom cell at different thicknesses (b) Thickness of top CZTS cell matched with different thickness of bottom CZTSe cell (c) Current density and open circuit voltage curve for tandem structure with current matched top and bottom cell at different bottom cell thickness (d) Tandem structure efficiency at different bottom cell thickness	74
7.14	(a) Current-voltage characteristics and (b) quantum efficiency for CZTS top cell CZTSe bottom cell and CZTS/CZTSe tandem cell	74
8.1	CZGS/Se crystal structure for (a) kesterite phase (Space group I-4) and (b) stannite phase (Space group I-4 2m) showing cations at the center of tetrahedron and chalcogens at the corner of tetrahedron	78
8.2	Volume optimization data, fitted with Murnaghan equation of state for (a) CZGS and (b) CZGSe in kesterite and stannite crystallographic phase	79
8.3	Band structure of CZGS/Se system for (a) kesterite CZGS, (b) stannite CZGS, (c) kesterite CZGSe and (d) stannite CZGSe	81
8.4	Total density of states and projected density of states for (a) kesterite CZGS (b) stannite CZGS (c) kesterite CZGSe (d) Stannite CZGSe	81
8.5	Dielectric constants as a function of energy for kesterite and stannite CZTS/Se phases: (a) real xx component; (b) real zz component; (c) imaginary xx component and (d) imaginary zz component	82
8.6	Refractive index and extinction coefficient for CZGS/Se in kesterite and stannite phases (a) n_{xx} (b) n_{zz} (c) k_{xx} and (d) k_{zz}	84
8.7	Optical absorption and optical conductivity of CZGS/Se in kesterite and stannite phase (a) α_{xx} (b) α_{zz} (c) σ_{xx} and (d) σ_{zz}	85
8.8	(a) Optical band gap of kesterite and stannite phase CZGS/Se after scissor correction of 1 eV in mBJ calculation (b) Birefringence in kesterite and stannite phase CZGS/Se	86
8.9	Reflectivity components as a function of energy for kesterite and stannite CZGS/Se phases in (a) perpendicular R_{xx} and (b) parallel R_{zz} to tetragonal c-axis	86