

List of Tables

<i>Table</i>	<i>Title</i>	<i>page</i>
1.1	Present status of achieved laboratory solar cell efficiency for different generation of photovoltaic technology	2
2.1	Secondary phases in CZTS system with their bandgap, type of conductivity and their influence on the material properties	11
2.2	Conduction band offset (CBO), Valance band offset (VBO) and the type of heterostructure interface for different buffer layer combination with CZTS,Se heterostructure	14
2.3	Compound to be etched with etchant solution, concentration and time required for etching	16
2.4	Intermediate layer with their thickness and impact on device parameters	17
4.1	Probable reaction path for CZTS formation	33
4.2	2θ value for (1 1 2) crystallographic plane, FWHM, average crystallite size, dislocation density, strain, stacking fault probability for CZTS thin film prepared with different routes and different annealing conditions	35
5.1	Crystallographic data of CZTS thin film obtained from the XRD measurement.	43
6.1	Elemental composition for S1 and S2 samples, as extracted from EDX measurements, in conjunction with different atomic ratios	56
6.2	Average, RMS roughness and grain size for S1 and S2 samples	56
6.3	Isomer and Quadrupole shifts with FWHM and tin valance state parameters derived from ^{119}Sn Mossbauer data	58
6.4	Activation energies for thermally activated and NNH carriers, as estimated from temperature dependent resistivity measurements	59
6.5	Photovoltaic device parameters, estimated from the measured photovoltaic response for devices based on S1 and S2 absorbers	61
7.1	Material parameters, used in the present work for simulating single junction and tandem solar cell structures	64
7.2	CZTS and CZTSe cell performance with single cell and in the tandem configuration	75
8.1	Lattice parameter, bond length and anion S/Se atomic positions for CZGS/Se kesterite and stannite crystallographic phases	79
8.2	Dielectric constants along c-axis $\epsilon_{ }$ (ϵ_{zz}) and perpendicular to c-axis ϵ_{\perp} (ϵ_{xx}), static dielectric constant ϵ_0 , refractive index n , extinction coefficient, Δn , mBJ band gap values $E_{g_{\text{mBJ}}}$, band gap values after scissor corrections $E_{g_{\text{mBJ scissor}}}$ and experimental values $E_{g_{\text{Experimental}}}$ from literature for comparison.	83