

Contents

| | |
|---|------|
| Abstract | page |
| Acknowledgements | i |
| Contents | iii |
| List of Figures | v |
| List of Tables | vii |
| List of Symbols | viii |
| List of Abbreviations | xiii |
| Chapter 1: Introduction | xv |
| 1.1 Principle of SMC control | 1 |
| 1.2 Principle of ISM control | 5 |
| 1.3 Motivation and Research Objectives | 5 |
| 1.4 Organization of Thesis | 7 |
| 1.5 Publications | 9 |
| | 10 |
| Chapter 2: Literature Review | 11 |
| 2.1 Minimum Size of Capacitance Required at the DC-link to Absorb 2ω –Ripple and Consequences of 2ω –Ripple on System | 11 |
| 2.1.1 <i>Minimum Size of Capacitance Required at the DC-link to Absorb 2ω–Ripple</i> | 11 |
| 2.1.2 <i>Consequences of 2ω–Ripple on System</i> | 13 |
| 2.2 Single-phase Inverter Topologies and Associates 2ω –Ripple Problem | 15 |
| 2.3 Classification of Ripple Mitigation Methods | 16 |
| 2.3.1 <i>Passive power-Decoupling Techniques</i> | 16 |
| 2.3.2 <i>Active Power-Decoupling Techniques</i> | 18 |
| 2.3.3 <i>Control-Oriented Compensation Techniques (CCTs) for Inverters with Front-end Converters or Control Circuits</i> | 27 |
| 2.3.4 <i>Some Other Topologies and Techniques</i> | 38 |
| 2.4 Conclusive Discussion and Open Challenges | 41 |
| | 41 |
| Chapter 3: Mitigation of SHC-ripple in Two-Stage DC-DC-AC Converter: An Adaptive-Sliding Mode Control Approach | 49 |
| 3.1 Concept of the Output Impedance Shaping | 50 |
| 3.2 Proposed Controller and its Role in the Output Impedance Shaping | 51 |
| 3.2.1 <i>Proposed Adaptive Switching Function</i> | 51 |
| 3.2.2 <i>Control Law</i> | 53 |
| 3.2.3 <i>Output Impedance Shaping of Front-End Converter</i> | 53 |
| 3.3 Stability and Transient Response Analysis | 54 |
| 3.3.1 <i>Existence of Sliding Mode</i> | 54 |
| 3.3.2 <i>Stability of the Sliding Mode</i> | 54 |
| 3.3.3 <i>Transient Response Analysis</i> | 56 |
| 3.3.4 <i>System Robustness Analysis</i> | 57 |
| 3.4 Simulation Results | 58 |
| 3.5 Experimental Results | 62 |
| 3.6 Summary | 66 |
| | 66 |
| Chapter 4: Mitigation of SHC-ripple in q-SBI: A Modified Adaptive-SMC Approach | 69 |
| 4.1 Quasi-Switched Boost Inverter and Its Modeling | 71 |
| 4.1.1 <i>Development of Average State Space Model</i> | 72 |
| 4.1.2 <i>Average Dynamic Model</i> | 73 |
| 4.1.3 <i>Calculation of the Reference Inductor Current</i> | 73 |
| 4.2 Output Impedance Shaping | 73 |
| 4.2.1 <i>Proposed Controller</i> | 75 |
| 4.2.2 <i>Control Law</i> | 76 |
| 4.2.3 <i>Shaping of $Z_{out_{A-B}}$ using Control Parameter α</i> | 76 |
| 4.2.4 <i>Existence of the Sliding Mode</i> | 77 |
| 4.2.5 <i>Stability of the Sliding Mode</i> | 78 |
| 4.2.6 <i>Robustness Analysis</i> | 79 |
| 4.3 Simulation Results | 81 |

| | | |
|---|---|------------|
| 4.3.1 | Steady-State Operation | 81 |
| 4.3.2 | Transients Response | 82 |
| 4.4 | Experimental Results | 84 |
| 4.5 | Summary | 88 |
| Chapter 5: Mitigation of SHC-ripple in the DC-DC-AC Converter: An ISM Based Control Approach | | 89 |
| 5.1 | Dynamic Model of the System | 90 |
| 5.2 | Dual-Loop Control for SHC Ripple Minimization | 91 |
| 5.2.1 | Dual-loop PID Controller Design | 91 |
| 5.3 | Proposed ISM Based Controller | 93 |
| 5.3.1 | Adaptive PID Controller | 93 |
| 5.3.2 | ISM based Controller (The Overall Control) | 94 |
| 5.3.3 | Existence of Sliding Mode | 94 |
| 5.3.4 | Stability | 95 |
| 5.3.5 | Design Example | 95 |
| 5.4 | Simulation Results | 98 |
| 5.4.1 | Analysis on Ripple-Reduction and System Dynamics Using Conventional Control | 98 |
| 5.4.2 | Analysis on Ripple-Reduction and System Dynamics Using Proposed ISM Based Control | 100 |
| 5.5 | Experimental Results | 102 |
| 5.6 | Summary | 105 |
| Chapter 6: Second-order Ripple in a DC Microgrid | | 107 |
| 6.1 | Derivation of Second-order Ripple in Small Signal Sense | 107 |
| 6.2 | Development of Equivalent Circuit | 108 |
| 6.2.1 | Large Signal Average Model | 108 |
| 6.2.2 | Linear Equivalent Circuit | 108 |
| 6.2.3 | Calculation of Current Ripple Injected at Input | 109 |
| 6.3 | Ripple Analysis for Island DC Microgrid | 111 |
| 6.3.1 | Ripple Injected into DC Bus by Down Stream Inverter loads | 113 |
| 6.3.2 | Ripple Injected into DC Sources by DC Bus | 114 |
| 6.4 | Results | 115 |
| 6.5 | Phase-Adjustment Based Ripple Control | 117 |
| 6.5.1 | Simulation Results | 119 |
| 6.6 | Summary | 121 |
| Chapter 7: Discussion and Conclusion | | 123 |
| References | | 127 |