

## List of Figures

Figures	Title	page
1.1	Power System Layout	1
1.2	Transmission Line Shunt Faults	2
1.3	Block Diagram of Numerical Relay	4
1.4	Block diagram for Wavelet Decomposition	6
1.5	Model of Artificial Neural Network	8
2.1	Fault Analysis Strategy	13
2.2	Modules for transmission line protection	13
3.1	System under consideration	23
3.2	Comparison windows for alienation coefficients: (a) Without Fault, and (b) With Fault at $t_0$	24
3.3	Flow chart of proposed scheme	25
3.4	Detection of AG Fault: (a) Three-phase currents at Bus-1, (b) Three-phase currents at Bus-2, (c) Approximate Coefficients for Phase-A current at Bus-1, (d) Approximate Coefficients for Phase-A current at Bus-2, (e) Alienation Coefficients of approximate coefficients at Bus-1, (f) Alienation Coefficients of approximate coefficients at Bus-2, (g) Fault Index variation with time	26
3.5	Variation of Fault Index with time: (a) BG Fault, (b) CG Fault, (c) AB Fault, (d) BC Fault, (e) AC Fault, (f) ABG Fault, (g) BCG Fault, (h) ACG Fault	27
3.6	Variation of Fault Index with time for ABCG fault	28
3.7	Discrimination between AB and ABG Fault	28
3.8	Variation of fault index with distance for three phase currents: (a) AG Fault, (b) AB Fault, (c) ABG Fault, (d) ABCG Fault	29
3.9	Variation of fault index for varying fault incidence angle (FIA): (a) AG Fault, (b) AB Fault, (c) ABG Fault, (d) ABCG Fault	29
3.10	Variation of fault index with time for fault impedance of $15\Omega$ : (a) AG Fault, (b) BG Fault, (c) CG Fault, (d) AB Fault, (e) BC Fault, (f) AC Fault	33
3.11	Variation of fault index with time for fault impedance of $15\Omega$ for: (a) ABG Fault, (b) BCG Fault, (c) ACG Fault, (d) ABCG Fault	34
3.12	Variation of fault index with time for fault impedance of $15\Omega$ : (a) ABG Fault, (b) BCG Fault, (c) ACG Fault, (d) ABCG Fault	35
3.13	ANN Architecture	36
4.1	Proposed System	39
4.2	Flowchart for fault detection and classification	40
4.3	Flowchart for Fault Location and Faulty Section Identification	41
4.4	Demonstration of AG fault detection: (a) Bus-1 Current Signals, (b) Bus-2 Current Signals, (c) Bus-3 Current Signals, (d) Differential Current, (e) Approximate Coefficients of Phase-A Differential Current, (f) Fault Index variation	42
4.5	Fault index variation for different faults: (a) BG Fault, (b) CG Fault, (c) AB Fault, (d) BC Fault, (e) AC Fault, (f) ABG Fault, (g) BCG Fault, (h) ACG Fault, (i) ABCG Fault	43
4.6	Discrimination between LL and LLG Fault	44
4.7	Fault Index variation w.r.t. distance for faults in different sections: (a) AG Fault, (b) AC Fault, (c) ABCG Fault	44
4.8	Fault Index variation w.r.t. fault incidence angle for faults in different sections: (a) BG Fault, (b) BCG Fault, (c) ABCG Fault	45
4.9	Fault index variation w.r.t time for high impedance faults: (a) AG Fault, (b) BG Fault, (c) CG Fault, (d) AB Fault	48
4.10	Fault index variation w.r.t time for high impedance faults: (a) BC Fault, (b) AC Fault, (c) ABG Fault, (d) BCG Fault, (e) ACG Fault, (f) ABCG Fault	49
4.11	Fault index variation w.r.t time, for noise effects: (a) AG Fault, (b) ABG Fault, (c) ABCG Fault	50
4.12	ANN Architecture	50
4.13	Five-terminal transmission system	52
4.14	Fault Index variation with time for different faults: (a) AG Fault in section 5-P <sub>4</sub> , (b) AB Fault in section 4-P <sub>4</sub> , (c) ABG Fault in section 2-P <sub>2</sub> and (d) ABCG Fault in section 1-P <sub>2</sub>	53
5.1	Flow chart of proposed scheme	58
5.2	STATCOM-Compensated Transmission System	58
5.3	Demonstration of AG Fault Detection: (a) Three-phase Current Signals at bus-1, (b) Three-phase Current Signals at bus-2, (c) Approximate Coefficients of bus-1 current signals, (d)	59

	Approximate Coefficients of bus-2 current signals, (e) Alienation Coefficients of app. coefficients at Bus-1, (f) Alienation Coefficients of app. coefficients at Bus-2, (g) Fault Index variation with time	
5.4	Variation of Fault Index with time: (a) BG Fault, (b) CG Fault, (c) AB Fault, (d) BC Fault, (e) AC Fault, (f) ABG Fault	60
5.5	Variation of Fault Index with time (a) BCG Fault, (b) ACG Fault, (c) ABCG Fault	61
5.6	Variation of Ground fault index with time	61
5.7	Variation of fault index with distance: (a) AG Fault, (b) AB Fault, (c) ABG Fault, (d) ABCG Fault	62
5.8	Variation of fault index for varying fault incidence angle (FIA): (a) AG Fault, (b) AB Fault, (c) ABG Fault, (d) ABCG Fault	63
5.9	Variation of fault index for fault impedance of 100Ω: (a) AG Fault, (b) BG Fault, (c) CG Fault, (d) AB Fault, (e) BC Fault, (f) AC Fault	67
5.10	Variation of fault index for fault impedance of 100Ω: (a) ABG Fault, (b) BCG Fault, (c) ACG Fault, (d) ABCG Fault	68
5.11	Fault Index variation for STATCOM installed at bus-2: (a) AG Fault, (b) AB Fault, (c) ABG Fault, (d) ABCG Fault	69
5.12	Fault Index variation for Noisy environment: (a) AG Fault, (b) AB Fault, (c) ABG Fault, (d) ABCG Fault	69
5.13	ANN Structure	70
5.14	TCSC-Compensated Transmission System	73
5.15	Demonstration of AG-Fault Detection: (a) Bus-1 Current Signals, (b) Bus-2 Current Signals, (c) Approximate Decomposition of Bus-1 Current Signals, (d) Approximate Decomposition of Bus-2 Current Signals, (e) Alienation Coefficients for Approximate Coefficients of Bus-1, (f) Alienation Coefficients for Approximate Coefficients of Bus-2	74
5.16	Fault Index Variation w.r.t. time for AG Fault	75
5.17	Fault Detection and Classification: (a) BG Fault, (b) CG Fault, (c) AB Fault, (d) BC Fault	75
5.18	Fault Detection and Classification: (a) AC Fault, (b) ABG Fault, (c) BCG Fault, (d) ACG Fault, (e) ABCG Fault	76
5.19	Ground Fault Index Variation	77
5.20	Fault Index variation for different locations: (a) AG Fault, (b) AB Fault, (c) ABG Fault, (d) ABCG Fault	77
5.21	Variation of Fault Incidence Angle: (a) AG Fault, (b) AB Fault, (c) ABG Fault, (d) ABCG Fault	78
5.22	Fault Index Variation for high impedance faults: (a) AG Fault, (b) BG Fault, (c) CG Fault, (d) AB Fault, (e) BC Fault, (f) AC Fault	82
5.23	Fault Index Variation for high impedance faults: (a) ABG Fault, (b) BCG Fault, (c) ACG Fault, (d) ABCG Fault	83
5.24	Fault Index Variation for TCSC installed at receiving end: (a) AG Fault, (b) AB Fault, (c) ABG Fault, (d) ABCG Fault	83
5.25	Fault Index Variation in Noisy Environment: (a) AG Fault, (b) AB Fault, (c) ABG Fault, (d) ABCG Fault	84
5.26	ANN Structure	85
5.27	UPFC-Compensated Transmission System	88
5.28	Demonstration of AG-Fault Detection: (a) Bus-1 Current Signals, (b) Bus-2 Current Signals, (c) Approximate Decomposition of Bus-1 Current Signals, (d) Approximate Decomposition of Bus-2 Current Signals, (e) Alienation Coefficients for Approximate Coefficients of Bus-1, (f) Alienation Coefficients for Approximate Coefficients of Bus-2, (g) Fault Index Variation	89
5.29	Fault Detection and Classification: (a) AB Fault, (b) ABG Fault, (c) ABCG Fault	90
5.30	Ground Fault Index variation with time	90
5.31	Fault Index variation for different locations: (a) AG Fault, (b) AB Fault, (c) ABG Fault, (d) ABCG Fault	91
5.32	Variation of Fault Incidence Angle: (a) AG Fault, (b) AB Fault, (c) ABG Fault, (d) ABCG Fault	92
5.33	Fault Index Variation for high impedance faults: (a) AG Fault, (b) AB Fault, (c) ABG Fault, (d) ABCG Fault	96
5.34	Fault Index Variation for UPFC installed at bus-2: (a) AG Fault, (b) AB Fault, (c) ABG Fault, (d) ABCG Fault	96
5.35	Fault Index variation for Noisy environment: (a) AG Fault, (b) AB Fault, (c) ABG Fault, (d) ABCG Fault	97
5.36	ANN Structure	98