

List of Figures

Figures	Title	Page
2.1	(a) Schematic representation for air mass ratio (AM) definition (b) Solar irradiance versus wavelength curve for AM1.5G terrestrial, extraterrestrial and black body radiation at 5777 K (sun surface Temp.)	8
2.2	Solar spectrum at air mass 1.5 and black body radiation at temperature 400°C, 500°C and 600°C calculated using plank's law [Duffie and Beckman, 1991]. Green dash line represents ideal absorptance in Uv-Vis-NIR range and thermal emittance in IR range.	8
2.3	Schematic of different spectrally selective absorber coatings	22
3.1	The schematic of thermal evaporator used for silver deposition	26
3.2	(a) Electrodeposition experimental schematic of nickel and black chrome layers and (b) Deposited BC/Ni/Cu schematic	27
3.3	RF/DC sputtering system schematic image	28
3.4	Camera image of X-ray diffractometer at IIT Jodhpur	30
3.5	Optical image of scanning electron microscope used for amylases microscopic structure at IIT Jodhpur	30
3.6	Optical image of scanning probe microscope (XE-70) at IIT Jodhpur	31
3.7	Camera image of Cary 4000 UV- Vis spectrophotometer	32
3.8	Optical image of FTIR spectrometer used for reflectance measurement at IIT Jodhpur	32
3.9	Image of Raman spectrometer unit at IIT Jodhpur	33
3.10	Schematic image of electrochemical polarization experiment for corrosion measurements	34
4.1	3 D view of radiation calorimeter (RADCAL) showing reflector (2) and absorbing surface (3) [Verma et al., 2018].	35
4.2	(a) Thickness with time graph (b) Emissivity with thickness graph of Ni/Cu structure	37
4.3	(a) Thickness with current density (b) Thickness with time and (c) Emissivity with thickness graph for BC/Ni/Cu structures	37
4.4	(a, b & c) Optical image of absorber surface coated with black chrome	38
4.5	The XRD plot of deposited BC/Ni/Cu structure	39
4.6	(a, b) Optical image (c, d) SEM image (e, f) 3- D topographic image of Ni/Cu and BC/Cu/N structure	39
4.7	(a) Reflectance versus wavelength plot of BC on nickel coated Cu substrate (b) heating cycle schematic (c) Reflectance versus wavelength plot of BC/Ni/Cu-HT (d) Reflectance versus wavelength plot of BC/Ni/Cu and BC/Ni/Cu-HT.	41
A.1	Optical image of silver deposited conical reflector surface	43
A.2	The XRD spectrum of Ag thin film coated on copper substrate (Ag/Cu)	44
A.3	(a, b) Camera image (c, d) SEM image (e, f) 3-D AFM image of pristine copper and silver deposited copper	46
A.4	Reflectance versus wavelength plot of (a) Ag/Cu (flat surface) (b) Ag/Cu (inclined surface) [inset: camera image of conical reflecting surface.]	46
5.1	Schematic view of each step explaining the growth of nanoporous alumina structure on Al substrate	48
5.2	Reflectance with wavelength plot of samples deposited for different time duration	48
5.3	X-ray diffraction (XRD) plot of Sample A, Sample B, Sample C and Sample D samples	49
5.4	SEM images for (a) Sample A (b) Sample B (c) Sample C and (d) Sample D and elemental composition shown in inset. Inset FESEM image shows the nonoporous structure and its size	50
5.5	Three dimensional AFM topographic images of (a) Sample A (b) Sample B (c) Sample C and (d) Sample D with measured surface roughness	51
5.6	Raman spectrum of (a) Sample A (b) Sample B (c) Sample C and (d) Sample D at room temperature	52
5.7	Reflectance plot with wavelength of Sample A, Sample B, Sample C and Sample D in IR range together with inset showing reflectance in UV-Vis range	53
5.8	(a) Heat treatment schematic and (b) temperature profile, used for thermal cycling for fabricated Sample A	54
5.9	(a) Potential Vs current density plot for Sample A, Sample B and Sample E (b) reflectance	54

	plot with wavelength in IR range for sample B and Sample D	
5.10	(a) Nyquist and (b) Bode plots of Sample A, Sample B and Sample E	55
5.11	Equivalent circuit Sample A, Sample B and Sample E	56
6.1	Emittance versus temperature of W/SS (Sample A) and (b) W/SS (Sample B) (c) emittance versus thickness	59
6.2	XRD plot of W/SS fabricated thin film (a) Sample A and (b) Sample B	61
6.3	(a) SEM images of W/SS fabricated thin film (a) Sample A and (b) Sample B	61
6.4	3-D topographic image of W/SS fabricated thin film (a) Sample A and (b) Sample B	61
6.5	Reflectance plot with wavelength of W/SS fabricated thin film (a) Sample A and (b) Sample B	62
6.6	(a) The schematic of UV-Vis absorption for W/SS Sample A and Sample B thin films and (b) an schematic diagram, showing tungsten oxide band gap and tungsten intraband energy levels with spin-orbit coupling	63
6.7	(a) Refractive index 'n' with wavelength and (b) extinction coefficient 'k' versus wavelength plot of W/SS sample A and sample B	63
7.1	Schematic image of dip coating process for thin film fabrication	66
7.2	Reflectance plot with wavelength for different sample in (a) UV-Vis (0.3-0.9 μm) and (b) IR range (2.5-25 μm)	67
7.3	Optical image of SS tube (a) before coating (b) during coating (c) after coating	67
7.4	XRD plot of fabricated $\text{SiO}_2/(\text{ZnO}/\text{Sn-In}_2\text{O}_3)_{n=4}/\text{SS}$ multilayer structure	68
7.5	3-D AFM image of (a) pristine SS substrate (b) Fabricated $\text{SiO}_2/(\text{ZnO}/\text{Sn-In}_2\text{O}_3)_{n=4}/\text{SS}$ (c) Heat treated and (d) corrosion treated sample	69
7.6	Reflectance versus wavelength plot of fabricated SSAC layer (Sample A), heat treated (Sample B) and corrosion treated (Sample C)	70
7.7	Schematic of (a) Box furnace used for heating (b) Heating cycle of sample	70
7.8	(a) Schematic representation of corrosion experiment (b) (a) Potential Vs current density plot for pristine SS and $\text{SiO}_2/(\text{ZnO}/\text{Sn-In}_2\text{O}_3)_{n=4}/\text{SS}$	71
A.1	Electrically connected controller, micro-stepper motor driver and stepper motor	75
A.2	(a) Schematic image of assembled dip coating system (b) Actual image of dip coating system made at IIT Jodhpur	76