

Bibliography

- Abe, A., (2009), "Trajectory planning for residual vibration suppression of a two-link rigid-flexible manipulator considering large deformation," *Mechanism and Machine Theory*, 44(9), 1627-1639.
- Abe, A., and Hashimobo, K., (2015), "A novel feedforward control technique for a flexible dual manipulator," *Robotics and Computer-Integrated Manufacturing*, 35, 169-177.
- Abe, A., and Yoshida, K., (2012), "Study on residual vibration suppression for a flexible dual-manipulator," 20th Mediterranean Conference on Control & Automation (MED), July 3-6, 321-326.
- Abedi, E., Nadooshan, A.A., and Salehi, S., (2008), "Dynamic modeling of two flexible link manipulators," *World Academy of Science, Engineering and Technology*, 22.
- Ahmad, M.A., Mohamed, Z., and Hambali, N., (2008), "Dynamic modeling of a two-link flexible manipulator system incorporating payload," 3rd IEEE Conference on Industrial Electronics and Applications, 3-5.
- Ahmad, M.A., Mohamed, Z., and Ismail, Z.H., (2009), "Dynamic modeling of a two-link flexible manipulator system incorporating payload," *The Institution of Engineers, Malaysia*, 72 (3), 56-62.
- AL-Bedoor, B.O., EL-Sinawi, A., and Hamdan, M.N., (2002), "Hybrid input shaping and PID control of a flexible robot manipulator," *Journal of Sound and Vibration*, 251(5), 767-781.
- Alhaddad, M., Shaukifeh, B., and Joukhadar, A., (2019), "Adaptive LQ-based computed-torque controller for robotic manipulator," *IEEE Conference of Russian Young Researchers in Electrical and Electronic Engineering (EIConRus)*, Saint Petersburg and Moscow, Russia, 2169-2173.
- Al-Solihat, M.K., Nahon, M., and Behdinan, K., (2018), "Three-dimensional nonlinear coupled dynamic modeling of a tip-loaded rotating cantilever," *Journal of Vibration and Control*, 24(22), 5366-5378.
- Anderson, G.L., (1978), "Natural frequencies of a cantilever with an asymmetrically attached tip mass," *AIAA Journal*, 16, 281-282.
- Ashayeri, A., Eghtead, M., and Farid, M., (2008), "Trajectory tracking for two-link flexible arm via two-time scale and boundary control methods," *ASME, International Mechanical Engineering Congress and Exposition*, October 31- November 6.
- Ata, A.A., Fares, W.F., and Sa'adeh, M.Y., (2012), "Dynamic analysis of a two-link flexible manipulator subject to different sets of conditions," *Procedia Engineering*, 41, 1253-1260.
- Auciello, N.M., (1996), "Transverse vibrations of a linearly tapered cantilever beam with tip mass of rotatory inertia and eccentricity," *Journal of Sound and Vibration*, 194(1), 25-34.
- Bai, M., Zhou, D.H., and Schwarz, H., (1998), "Adaptive Augmented State Feedback Control for an Experimental Planar Two-Link Flexible Manipulator," *IEEE Transactions on Robotics and Automation*, 14(6).
- Bai, S., Tzvi, P.B., Zhou, Q., and Huang, X., (2008), "Dynamic modeling of a rotating beam having a tip mass," *IEEE, International Workshop on Robotic and Sensors Environments*, Ottawa, Canada, 17-18.
- Bakr, E.M., and Shabana, A.A., (1986), "Geometrically non-linear analysis of multi-body systems," *Computer and Structures*, 23, 739-751.
- Basher, H.A., (2007), "Modeling and simulation of flexible robot manipulator with a prismatic joint," *Proceedings 2007 IEEE Southeast Con*, Richmond, VA, 255-260.
- Bayo, E., (1987), "A finite element approach to control the end point of a single link flexible robot," *Journal of Robotic Systems*, 4, 63-75.
- Bayo, E., Papadopoulos, P., and Stubbe, J., (1989), "Inverse dynamics and kinematics of multi-link elastic robots: an iterative frequency domain approach," *The International Journal of Robotics Research*, 8(6), 49-62.

- Benati, M. and Morro, A., (1994), "Formulation of equations of motion for a chain flexible links using Hamilton's principle," Transactions of ASME, Journal of Dynamic Systems, Measurement, and Control 116, 81-88.
- Benosman, M., and Vey, G.L., (2002), "Joint trajectory tracking for planar multi-link flexible manipulator: simulation and experiment for a two-link flexible manipulator," Proceedings of IEEE International Conference on Robotics & Automation, Washington, DC.
- Bhat, B.R., and Wagner, H., (1976), "Natural frequencies of a uniform cantilever with a tip mass slender in the axial direction," Journal of Sound and Vibration, 45, 304-307.
- Bolandi, H., and Esmailzadeh, S.M., (2008), "Analytical modelling and nonlinear stain feedback control of a flexible robot arm," Automatic Control and Computer Sciences, 42 (5), 236-248.
- Book, W.J., (1984), "Recursive Lagrangian dynamics of flexible manipulator arms," International Journal of Robotics Research, 3, 87-101.
- Botsali, F.M., Tinkir, F.M., Kalyoncu, M., and Onen, U., (2010), "Fuzzy logic trajectory control of flexible robot manipulator with rotating prismatic joint," The 2nd International Conference on Computer and Automation Engineering (ICCAE), Singapore, 35-39.
- Cai, G., Hong, J., and Yang S.X., (2005), "Dynamic analysis of a flexible hub-beam system with tip mass," Mechanics Research Communications, 32, 173-190.
- Cannon, R.H., and Schmitz, E., (1984), "Initial experiments on end-point control of flexible one-link robot" The International Journal of Robotics Research, 3, 62-75.
- Cao, X.T., and Li, Y.C., (2008), "Robust RBF neural network force/position control of time varying constrained flexible manipulator," Control and Decision, 22, 977-982.
- Casti, C., and Messina, A., (2010), "Matrix formulations for solving the configuration-dependent eigenvalue problem of a two-link flexible manipulator," 19th International Workshop on Robotics in Alpe-Adria-Danube Region - RAAD.
- Casti, C., and Messina, A., (2011), "Vibration analysis of multilink manipulators based on Timoshenko beam theory," Journal of Robotics, vol. 2011, article ID 890258, 21.
- Cetinkunt, S., and Yu, W.L., (1991), "Closed-loop behavior of a feedback-controlled flexible arm: a comparative study," The International Journal of Robotics Research, 10, 262-275.
- Chalhoub, N.G., Kfoury, G.A., (2005), "Development of a robust nonlinear observer for a single-link flexible manipulator," Nonlinear Dynamics, 39, 217-233.
- Chen, W., (2001), "Dynamic modeling of multi-link flexible robotic manipulators," Computers & Structures, 79(2), 183-195.
- Chen, S., Zhang, D., and Liu, J., (2012), "Dynamic analysis of multi-link spatial flexible manipulator arms with dynamic stiffening effects," Theoretical & Applied Mechanics Letters 2, 063003.
- Cheng, J., Xu, H., and Yan, A., (2006), "Frequency analysis of a rotating cantilever beam using assumed mode method with coupling effect," Mechanics Based Design of Structures and Machines, 34, 25-47.
- Cheong, J., and Youm, Y., (2003), "System mode approach for analysis of horizontal vibration of 3-D two-link flexible manipulators", Journal of Sound and Vibration, 268(1), 49-70.
- Chiou, C., and Shahinpoor, M., (1990), "Dynamic stability analysis of a two-link force-controlled flexible manipulator," Transactions of ASME, Journal of Dynamic Systems, Measurement, and Control, 112(6), 661-666.
- Choi, S.B., (2006), "Vibration control of a smart beam structure subjected to actuator uncertainty: experimental verification," Acta Mechanica, 181, 19-30.
- Choudhury, A., and Genin, J., (1989), "Kinematics of an n-degree-of-freedom multi-link robotic system," The International Journal of Robotics Research, 8(6), 49-62.
- Choura, S., and Yigit, A.S., (2001), "Control of a two-link rigid-flexible manipulator with a moving payload mass," Journal of Sound and Vibration, 243(5), 883-897.
- Chung J., and Yoo, H.H., (2004), "Dynamic analysis of rotating cantilever beam using the finite element method," Journal of Sound and Vibration, 249, 147-164.
- Coleman, M.P., (1998), "Vibration eigenfrequency analysis of a single-link flexible manipulator," Journal Sound and Vibration, 212, 107-120.
- Coleman, M.P., and McSweeney, L.A., (2004), "Analysis and computation of the vibration spectrum of the Cartesian flexible manipulator," Journal of Sound and Vibration, 274(1): 445-454.

- Damaren, C.J., (1998), "Modal properties and control system design for two-link flexible manipulators," *The International Journal of Robotics Research*, 17(6), 667-678.
- Demydyuk, M.V., and Hoshovs'ka, N.V., (2019), "Parametric optimization of the transport operations of a two-link manipulator," *Journal of Mathematical Sciences*, 238(2), 174-188.
- Ding, W., Deng, H., Li, Q., and Xia, Y., (2014), "Control-orientated dynamic modeling of forging manipulators with multi-closed kinematic chains," *Robotics and Computer-Integrated Manufacturing*, 30, 421-431.
- Ding, W., and Shen, Y., (2017), "Analysis of transient deformation response for flexible robotic manipulator using assumed mode method," 2nd Asia-Pacific Conference on Intelligent Robot Systems.
- Ding, X., and Selig, J.M., (2004), "Lumped parameter dynamic modelling for flexible manipulator," Fifth World Congress on Intelligent Control and Automation (IEEE Cat. No. 04EX788), 1, 280-284.
- Dogan, M., and Morgul, O., (2010), "On the control of two-link flexible robot arm with non-uniform cross section," *Journal of Vibration and Control*, Vol. 16, Issue 5, 619-646.
- Dou, H., and Wang, S., (2013), "Robust adaptive motion/force control for motion synchronization of multiple uncertain two-link manipulators," *Mechanism and Machine Theory*, 67, 77-93.
- Dwivedy, S.K., and Eberhard, P., (2006) "Dynamic analysis of flexible manipulators, a literature review," *Mechanism and Machine Theory*, 41, 749-777.
- Dwivedy, S.K., and Kar, R.C., (1999), "Nonlinear response of a parametrically excited system using higher order method of multiple scales," *Nonlinear Dynamics*, 20, 115-130.
- Endo, K., and Yabuno, H., (2012), "Swing-up control of a three-link underactuated manipulator by high-frequency horizontal excitation," *Transactions of ASME, Journal of Computational, and Nonlinear Dynamics*, 8(1).
- Emam, S.A., (2007), "Vibrations of a flexible-link flexible-base robot arm," Proceedings of the ASME 2007 International Design Engineering Technical Conferences & Computers and Information in Engineering Conference, IDETC/CIE, September 4-7, Las Vegas, Nevada, USA.
- Emam, S.A., (2010), "Dynamics of a flexible-hub geometrically nonlinear beam with a tip mass," *Journal of Vibration and Control*, 16(13), 1989 - 2000.
- Esfandiar, H., and Daneshmand, S., (2012), "Complete dynamic modeling and approximate state space equations of the flexible link manipulator," *Journal of Mechanical Science and Technology*, 26(9), 2845-2856.
- Esfandiar, H., and Korayem, M.H., (2015), "Accurate nonlinear modeling for flexible manipulators using mixed finite element formulation in order to obtain maximum allowable load," *Journal of Mechanical Science and Technology*, 29 (9), 3971-3982.
- Esmailzadeh, E., and Jazar, G.N., (1998), "Periodic behavior of a cantilever beam with end mass subjected to harmonic base excitation," *International Journal of Non-linear Mechanics*, 33, 567-577.
- Farid, M., and Cleghorn, W.L., (2014), "Dynamic modeling of multi-flexible-link planar manipulators using curvature-based finite element method," *Journal of Vibration and Control*, 20(11), 1682-1696.
- Frankovsky, P., Hroncova, D., Delyova, I., and Hudak, P., (2012), "Inverse and forward dynamic analysis of two link manipulator," *Procedia Engineering*, 48, 158-163.
- Fung, E.H.K., and Yau D.T.W., (2001), "Vibration frequencies of a rotating flexible arm carrying a moving mass," *Journal of Sound and Vibration*, 241(5), 857-878.
- Fung, R.F, and Chang, C., (1998), "Dynamic modeling of a non-linearly constrained flexible manipulator with a tip mass by Hamilton's principle," *Journal of Sound and Vibration*, 216(5), 751-769.
- Gandhi, P.S., and Vyas, V., (2017), "On the dynamics of tapered vibro-impacting cantilever with tip mass," *Journal of Mechanical Science and Technology*, 31(1), 63-73.
- Gawronski, W., Ih, C.H.C., and Wang, S.J., (2008), "On dynamics and control of multi-link flexible manipulators," *Journal of Dynamic Systems, Measurement, and Control*, 117, 2.
- Giorgio, I., and Vescovo, D.D., (2018), "Non-linear lumped-parameter modeling of planar multi-link manipulators with highly flexible arms," *Robotics*, 7(4), 60.
- Green, A., and Sasiadek, J.Z., (2004), "Dynamics and trajectory tracking control of a two-link robot manipulator," *Journal of Vibration and Control*, 10(10), 1415-1440.

- Guechi, E., Bouzoualegh, S., Messikh, L., and Blazic, S., (2018), "Model predictive control of a two-link robot arm," International Conference on Advanced Systems and Electric Technologies (IC_ASET), Hammamet, 409-414.
- Gunjal, S.K., and Dixit, U.S., (2007), "Vibration analysis of shape-optimized rotating cantilever beams," Engineering Optimization, 39, 105-123.
- Gurgoze, M., and Zeren, S., (2011), "The influences of both offset and mass moment of inertia of a tip mass on the dynamics of a centrifugally stiffened visco-elastic beam," Meccanica, 46(6), 1401-1412.
- Halim, D., Luo, X., and Trivailo, P.M., (2014), "Decentralized vibration control of a multi-link flexible robotic manipulator using smart piezoelectric transducers," Acta Astronautica, 104, 186-196.
- Hamdan, M.N., and El-Sinavi, A.H., (2005), "On the non-linear vibrations of an inextensible rotating arm with setting angle and flexible hub," Journal of Sound and Vibration, 281, 375-398.
- Hamed, Y.S., Alharthi, M.R., and AlKhathami, H.K., (2018), "Nonlinear vibration behavior and resonance of a Cartesian manipulator system carrying an intermediate end effector," Nonlinear Dynamics, 91, 1429-1442.
- Henmi, T., Deng, M., and Inoue, A., (2011), "Nonlinear control of the under actuated two-link manipulator using the sliding-mode type partial linearization method," International Journal of Computer Applications in Technology, 41(3/4).
- Hermle, M., and Eberhard, P., (2007), "Control and parameter optimization of flexible robots," Mechanics of Structures and Machines, 28(2-3), 137-168.
- Huang, J.S., Fung, R.F., and Tseng, C.R., (1999), "Dynamic stability of a cantilever beam attached to a translational/rotational base," Journal of Sound and Vibration, 224(2), 221-242.
- Hu, F.L., and Ulsoy, A.G., (1994), "Dynamic modeling of constrained flexible robot arms for controller design," Transaction of ASME, Journal of Dynamic Systems, Measurement, and Control, 116,56-65.
- Hwang, S.T., Broberg, H.L., and Guo, R.M., (1997), "Dynamic modelling of planar flexible multiple-link manipulators," International journal of modelling and simulation, 17(2), 151-159.
- Ju, J., Li, W., Fan, M., Wang, Y., and Yang, X., (2017), "Nonlinear modelling and dynamic stability analysis of a flexible Cartesian robotic manipulator with base disturbance and terminal load," Mechanical Sciences, 8, 221-234.
- Jun, W., Guang, Y., Ying, G., and Liping, W., (2018), "Mechatronics modeling and vibration analysis of a 2-DOF parallel manipulator in a 5-DOF hybrid machine tool," Mechanism and Machine Theory, 121, 430-445.
- Kaluarachchi, M.M., Ho, J., and Yahya, S., (2017), "Design of a single motor, tendon driven redundant manipulator with reduced driving joint torques," Mechanics Based Design of Structures and Machines, 46(5), 591-614.
- Kalyoncu, M., (2008), "Mathematical modelling and dynamic response of a multi-straight-line path tracing flexible robot manipulator with rotating-prismatic joint," Applied Mathematical Modelling, 32(6), 1087-1098.
- Karagulle, H., Malgaca, L., Dirilmis, M., Akdag, M., and Yavuz, (2015), "Vibration control of a two-link flexible manipulator," Journal of Vibration and Control, 23(12), 2023 - 2034.
- Khairudin, M., (2008), "Dynamic modeling of a flexible link manipulator robot using AMM," Telkomnika, 6(3), 185-190.
- Khairudin, M., Mohamed, Z., Husain, A.R., and Mamat, R., (2014), "Dynamic characterisation of a two-link flexible manipulator: theory and experiments," Advances in Robotics Research, 1(1), 061-079.
- Khorrani, F., (1989), "Analysis of multi-link flexible manipulators via asymptotic expansions," Proceedings of the 28th Conference on Decision and Control, Tampa, Florida, 2089-2094.
- Khorrani, F., Jain, S., and Tzes, A., (1994), "Experiments on rigid-body-based controllers with input preshaping for a two-link flexible manipulator," IEEE Transaction on Robotics and Automation, RA-10, 55-65.
- Kim, H., Choi, S., and Thompson, B.S., (2001), "Compliant control of a two-link flexible manipulator featuring piezoelectric actuators," Mechanism and Machine Theory, 36(3), 411-424.
- Kim, J.E., (2017), "On the equivalent mass-spring parameters and assumed mode of a cantilevered beam with a tip mass," Journal of Mechanical Science and Technology, 31(3), 1073-1078.

- Kojima, H., (1986), "Transient vibrations of a beam/mass system fixed to a rotating body," *Journal of Sound and Vibration*, 107(1), 149-154.
- Konno, A., Uchiyama, M., Kito, Y., and Murakami, M., (1997), "Configuration-dependent vibration controllability of flexible-link manipulator," *The International Journal of Robotic Research*, 16(4), 567-576.
- Korayem, M.H., Rahimi, H.N., and Nikoobin, A., (2012), "Mathematical modeling and trajectory planning of mobile manipulators with flexible links and joints," *Applied Mathematical Modelling*, 36, 3229-3244.
- Korayem, M.H., and Dehkordi, S.F., (2019), "Motion equations of cooperative multi flexible mobile manipulator via recursive Gibbs-Appell formulation," *Applied Mathematical Modelling*, January.
- Korayem, M.H., Heidari, A., and Nikoobin, A., (2009), "Effect of payload variation on the residual vibration of flexible manipulators at the end of a given path," *Transaction B: Mechanical Engineering*, 16 (4), 332-343.
- Kumar, P., and Pratiher, B., (2018), "Nonlinear modeling and vibration analysis of a two-link flexible manipulator coupled with harmonically driven flexible joints," *Mechanism and Machine Theory*, 131, 278-299.
- Kumar, P., and Pratiher, B., (2019), "Modal characterization with nonlinear behaviors of a two-link flexible manipulator", *Archive of Applied Mechanics*, <https://doi.org/10.1007/s00419-018-1472-9>.
- Kumar, P., and Pratiher, B., (2019), "Modal analysis and dynamic responses of a rotating Cartesian manipulator with generic payload and asymmetric load", *Mechanics based Machines and Structures*, <https://www.tandfonline.com/doi/abs/10.1080/15397734.2019.1624174>.
- Kumar, P., and Pratiher, B., (2018), "Modal identification and nonlinear vibration of flexible manipulator with revolute pair incorporating generic payload", *Proceedings of ASME 2018, IMECE 2018*.
- Kumar, P., and Pratiher, B., (2020), "Position analysis and nonlinear phenomena of flexible manipulator with generic payload mounted on a moving base", *IMECHE Part K: Journal of Multi-body Dynamics*, Sage, <http://doi.org/10.1177/146441920901389>.
- Kumar, P., and Pratiher, B., (2019), "Investigation of Parametric Influence on Control of a Two-link Flexible Manipulator Incorporating a Payload", *InaCoMM*, 2019.
- Kumar, P., and Pratiher, B., (2020), "Influences of generic payload and constraint force on modal analysis and dynamic responses of flexible manipulator," *Mechanics Based Design of Machines and Structures*, Accepted.
- Kumar, S., Mitra, A., and Roy, H., (2015), "Geometrically nonlinear free vibration analysis of axially functionally graded taper beams," *Engineering Science and Technology, an International Journal*, 18(4), 579-593.
- Lai, S.H.Y., (1994), "Geometrically nonlinear transient analysis of a rotating beam structure carrying a static payload," *Mechanics Research Communications*, 21(5), 473-482.
- Laura, P.A.A., Pombo, J.L., and Susemihl, E. A., (1974) "A note on the vibrations of a clamped-free beam with a mass at the free end," *Journal of Sound and Vibration*, 37, 161-168.
- Lee, H.P., (1995), "Stability of a cantilever beam with tip mass subjected to axial sinusoidal excitations," *Journal of Sound and Vibration*, 183, 91-98.
- Lee, J.D., and Wang, B., (1988), "Dynamic equations for a two-link flexible robot arm", *Computers and Structures*, 29(3), 469-477.
- Li, C.J., and Sankar, T.S., (1993), "Systematic methods for efficient modeling and dynamics computations of flexible robot manipulators," *IEEE Transaction on Systems, Man and Cybernatics*, SMC-23(1), 77-94.
- Liu, Y., Li, W., Yang, X., Fan, M., Wang, Y., and Lu, E., (2015), "Vibration response and power flow characteristics of a flexible manipulator with a moving base," *Shock and Vibration*, Article ID 589507, 8 pages.
- Lochan, K., and Roy, B.K., (2015), "Position control of two-link flexible manipulator using low chattering SMC techniques," *IJCTA*, 8(3), 1137-1145.

- Lochan, K., Roy, B.K., and Subudhi, B., (2016), "A review on two-link flexible manipulators," *Annual Reviews in Control*, 42, 346-367.
- Lochan, K., Roy, B.K., and Subudhi, B., (2016), "SMC controlled chaotic trajectory tracking of two-link flexible manipulator with PID sliding surface," *IFAC-PapersOnLine*, 49-1, 219-224.
- Lochan, K., Roy, B.K., and Subudhi, B., (2017), "Robust tip trajectory synchronisation between assumed modes modelled two-link flexible manipulators using second-order PID terminal SMC," *Robotics and Autonomous Systems*, 97, 108-124.
- Low, K.H., (1987), "A systematic formulation of dynamic equations for robot manipulators with elastic links," *Journal of Field Robotics*, 4(3), 435-456.
- Low, K.H., (1990), "Eigen-analysis of a tip-loaded beam attached to a rotating joint," *Journal of Vibration and Acoustics*, 112 (4), 497-500.
- Low, K.H., (1994) "Vibration analysis of a tip-loaded beam attached to a rotating joint," *Computers & Structures*, 52(5), 955-968.
- Low, K.H., and Ng, C.K., (1992), "An analysis program for vibration modes of a link carrying solid mass," *Computers & Structures*, 43(4), 775-785.
- Low, K.H. and Vidyasagar, M., (1998), "A Lagrangian formulation of the dynamic model for flexible manipulator systems," *Transactions of ASME, Journal of Dynamic Systems, Measurement, and control*, 110, 175-181.
- Luca, A.D., and Siciliano, B., (1991), "Closed-form dynamic model of a planar multi-link lightweight robots," *IEEE Transaction on Systems, Man and Cybernetics*, SMC-1, 826-39.
- Luo, Z., (1997), "Shear force feedback control of a single-link flexible robot with a revolute joint," *IEEE Transactions on Automatic Control*, 42(1), 53-65.
- Mahamood, H.M., and Pedro, J.O., (2011), "Hybrid PD/PID controller design for two-link flexible manipulators," *Proceedings of 2011 8th Asian Control Conference (ASCC)*, Kaohsiung, Taiwan, May 15-18.
- Malaeke, H., and Moenfarid, H., (2016), "Analytical modeling of large amplitude free vibration of non-uniform beams carrying a both transversely and axially eccentric tip mass," *Journal of Sound and Vibration*, 366, 211-229.
- Martins, J., Botto, M.A., and Sa da Costa, J., (2002), "Modelling flexible beams for robotic manipulators," *Multibody System Dynamics*, 7, 79-100.
- Matsuno, F., Asano, T., and Sakawa, Y., (1994), "Modeling and quasi-static hybrid position-force control of constrained planar two-link flexible manipulators," *IEEE Transactions on Robotics and Automation*, 10, 287-297.
- Maurizi, M.J., Belles, P., and Rosales, M.B., (1990), "A note on free vibrations of a constrained cantilever beam with a tip mass of finite length," *Journal of Sound and Vibration*, 138(1), 170-172.
- Mayo, J., Dominguez, J., and Shabana, A.A., (1995), "Geometrically nonlinear formulation of beams in flexible multi-body systems" *Journal of Vibration and Acoustics*, 117, 501-509.
- Meng, Q., Lai, X., Wang, Y., and Wu, M., (2018), "A fast stable control strategy based on system energy for a planar single-link flexible manipulator," *Nonlinear Dynamics*, published online, 02 June.
- Milford, R.I., and Asokanthan, S.F., (1999), "Configuration dependent eigenfrequencies for a two-link flexible manipulator: experimental verification," *Journal of Sound and Vibration*, 222(2), 191-207.
- Mishra, N., Singh, S.P., and Nakra, B.C. (2015), "Dynamic analysis of a single link flexible manipulator using Lagrangian-assumed modes approach," *International Conference on Industrial Instrumentation and Control (ICIC)*, 2015, 1144-1149.
- Mitchell, T.P., and Bruch Jr., J.C., (1988), "Free vibrations of a flexible arm attached to a compliant finite hub," *Transactions of ASME, Journal of Vibration, Acoustics, Stress, and Reliability in Design*, 110(1), 118-120.
- Moallem, M., Patel, R.V., and Khorasani, K., (1997), "An inverse dynamics control strategy for tip position tracking of flexible multi-link manipulators," *Journal of Robotic Systems*, 14(9), 649-658.
- Moradi, M., and Malekizade, H., (2013), "Neural network identification based multivariable feedback linearization robust control for a two-link manipulator," *Journal of Intelligent & Robotic Systems*, 72(2), 167-178.

- Na, K., and Kim, J., (2006), "Deployment of a multi-link flexible structure," *Journal of Sound and Vibration*, 294(1-2), 298-313.
- Nagaraj, B.P., Nataraju, B.S., and Ghosal, A., (1997), "Dynamics of a two-link flexible system undergoing locking: mathematical modelling and comparison with experiments," *Journal of Sound and Vibration* 207 (4) 567-589.
- Naganathan, G., and Soni, A.H., (1987), "Coupling effects of kinematics and flexibility in manipulators," *The International Journal of Robotics Research*, 6 (1), 75-84.
- Naguleswaran, S., (2006), "Vibration of an Euler-Bernoulli uniform beam carrying a rigid body at each end," *International Journal of Mechanical Engineering Education*, 34 (3), 194-210.
- Nayfeh, A.H., and Arafat, H.N., (1998), "Nonlinear response of cantilever beams to combination and subcombination resonances," *Shock and Vibration*, 5(5-6), 277-288.
- Nissing, D., (2002), "A vibration damped flexible robot: identification and parameter optimization," *Proceedings of American Control Conference*, Chicago, Illinois.
- Oakley, C. M., and Cannon Jr., R.H., (1989), "Theory and experiments in selecting mode shapes for two-link flexible manipulators," *Proceedings of the First International Symposium on Experimental Robotics*, Montreal, Canada.
- Oguamanam, D.C.D., (2003), "Free vibration of beams with finite mass rigid tip load and flexural-torsional coupling," *International Journal of Mechanical Sciences*, 45, 963-979.
- Oguamanam, D.C.D., and Arshad, M., (2005), "On the natural frequencies of a flexible manipulator with a tip payload", *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*, 219(11), 1199 - 1205.
- Oh, S., and Kong, K., (2015), "Two-degree-of-freedom control of a two-link manipulator in the rotating coordinate system," *IEEE Transactions on Industrial Electronics*, 62(9).
- Ower, J.C., and Van De Vegte, J., (1987), "Classical control design for a flexible manipulator: Modeling and Control System Design," *IEEE Journal of Robotics and Automation*, RA, 3(5).
- Ozer, A., Semercigil, S.E., Kumar, R.P., and Yowat, P., (2013), "Delaying tool chatter in turning with a two-link robotic arm", *Journal of Sound and Vibration*, 332(6), 1405-1417.
- Pai, P.F., and Nayfeh, A.H., (1990), "Non-linear non-planar oscillations of a cantilever beam under lateral base excitations," *International Journal of Non-linear Mechanics*, 25, 455-474.
- Park, J., and Khatib, O., (2005), "Multi-link multi-contact force control for manipulators," *Proceedings of the 2005 IEEE International Conference on Robotics and Automation Barcelona*, Spain.
- Parks, T.R., and Pak, H.A., (1991), "Effect of payload on dynamics of a flexible manipulator-modeling and control," *Transaction of ASME, Journal of Dynamic Systems, Measurement, and Control*, 113, 409-418.
- Pedro, J.O., and Tshabalala, T., (2015), "Hybrid NNMPD/PID control of a two-link flexible manipulator with actuator dynamics," *10th Asian Control Conference (ASCC)*, Kota Kinabalu, 1-6.
- Perez P.J., Perez, J.P., Soto, R., Flores, A., Rodriguez, F., and Meza, J.L., (2012), "Trajectory tracking error using PID control law for two-link robot manipulator via adaptive neural networks," *Procedia Technology*, 3, 139-146.
- Piedboeuf, J., and Moore, B., (2002), "On the foreshortening effects of a rotating flexible beam using different modeling methods," *Mechanics of Structures and Machines*, 30(1), 83-102.
- Pratiher, B., and Bhowmik, S., (2012), "Nonlinear response of a Cartesian robotic manipulator carrying an end-effector at an arbitrary position," *Nonlinear Dynamics*, 69, 539-553.
- Pratiher, B., and Dwivedy, S.K., (2007), "Nonlinear dynamics of a flexible single link Cartesian manipulator," *International Journal of Non-linear Mechanics* 42, 1062- 1073.
- Pratiher, B., and Dwivedy, S.K., (2007), "Parametric instability of a cantilever beam with magnetic field and periodic axial load," *Journal of Sound and Vibration*, 305, 904-917.
- Pratiher, B., and Dwivedy, S.K., (2008), "Non-linear dynamics of a flexible single link viscoelastic Cartesian manipulator," *International Journal of Non-linear Mechanics*, 43, 683-696.
- Pratiher, B., and Dwivedy, S.K., (2009), "Nonlinear vibration of magneto-elastic cantilever beam with tip mass," *Transactions of ASME, Journal of Vibration and Acoustics*, 131(2).

- Pratiher, B., and Dwivedy, S.K., (2010), "Nonlinear response of a soft magneto elastic cantilever beam with end mass under static and dynamics magnetic field," *Journal of Vibration and Control*, 17(9), 1394- 1406.
- Pratiher, B., and Dwivedy, S.K., (2011), "Nonlinear vibrations and frequency response analysis of a cantilever beam under periodically varying magnetic field," *Mechanics Based Design of Structures and Machines*, 39(3), 378-391.
- Pratiher, B., (2011), "Nonlinear response of a magnetoelastic translating beam with prismatic joint for higher resonance conditions," *International Journal of Non-linear Mechanics*, 46, 685-692.
- Poppelwell N., and Chang, D., (1996), "Influence of an offset payload on a flexible manipulator," *Journal of Sound and Vibration*, 190, 721-725.
- Qian, Z., Zhang, D., and Jin, C., (2018), "A regularized approach for frictional impact dynamics of flexible multi-link manipulator arms considering the dynamic stiffening effect," *Multibody System Dynamics*, 43, 229-255.
- Qiu, Z., (2012), "Adaptive nonlinear vibration control of a Cartesian flexible manipulator driven by a ballscrew mechanism," *Mechanical Systems and Signal Processing*, 30, 248-266.
- Rahmani, B., and Belkheiri, M., (2018), "Adaptive neural network output feedback control for flexible multi-link robotic manipulators," *International Journal of Control*, First online, 2018.
- Reddy, B.S., and Ghosal, A., (2015), "Nonlinear dynamics of a rotating flexible link," *Transaction of ASME, Journal of Nonlinear and Computational Dynamics*, 10(6), 061014-8.
- Reddy, B.S., Simha, K.R.Y., and Ghosal, A., (1999), "Free and forced vibration of a kinked cantilever beam," *Proceedings of DETC'99, ASME Design Engineering Technical Conference September 12-15, 1999*.
- Reddy, B.S., Simha, K.R.Y., and Ghosal, A., (1999), "Free vibration of kinked cantilever with attached masses," *Journal of Acoustical Society of America*, 105, 164-173.
- Saad, M., Akhrif, O., and Saydy, L., (2012), "Analytical model of one flexible link system with nonlinear kinematics," *Journal of Vibration and Control*, 19(12), 1795-1806.
- Sato, O., Sato, A., Takahashi, N., and Yokomichi, M., (2013), "Experimental analysis of the two-link-manipulator in consideration of the relative motion between link and object," *Proceedings of the 19th ISAROB*, 748-751.
- Sato, O., Sato, A., Takahashi, N., and Yokomichi, M., (2016), "Analysis of the two-link manipulator in consideration of the horizontal motion about object," *Artificial Life and Robotics*, 21(1), 43-48.
- Sayahkarajy, M., (2018), "Mode shape analysis, modal linearization, and control of an elastic two-link manipulator based on the normal modes," *Applied Mathematical Modelling*, 59, 546-570.
- Sayahkarajy, M., Supriyanto E., and Mohamed, Z., (2017), "Principal vibration modes of a rigid-flexible manipulator," *International Conference on Robotics, Automation and Sciences (ICORAS), Melaka, Malaysia*, 1-5.
- Shaker, M.C. and Ghosal, A., (2006), "Nonlinear modeling of flexible manipulators using non-dimensional variables," *Transaction of ASME, Journal of Nonlinear and Computational Dynamics*, 1, 123-134.
- Shawky, A., □□□Zydek, D., □□□Elhalwagy, Y.Z., and □□□Ordys, A., (2013), "Modeling and nonlinear control of a flexible-link manipulator," *Applied Mathematical Modelling*, 37, 9591-9602, 2013.
- Shin, H., and Rhim, S., (2015), "Modeling and control of lateral vibration of an axially translating flexible link," *Journal of Mechanical Science and Technology*, 29(1), 191-198.
- Spong, M.W., (1987), "Modelling and control of elastic joint robots", *Transaction of ASME, Journal of Dynamic Systems, Measurement, and Control*, 109, 310-319.
- Storch, J., and Gates, S., (1983), "Planar dynamics of a uniform beam with rigid bodies affixed to the ends," *Technical report CSDL-R- 1629, The Charles Stark Draper Laboratory, Cambridge, MA*.
- Subrahmanyam, P.K., and Seshu P., (1997), "Dynamics of a flexible five bar manipulator," *Computers & structures*, 63(2), 283-294.
- Sun, D., (2016), "Tracking accuracy analysis of a planar flexible manipulator with lubricated joint and interval uncertainty," *Transactions of ASME, Journal of Computational and Nonlinear Dynamics*, 11(5).

- Tadikonda, S.S.K., and Baruh, H., (1992), "Dynamics and control of a translating flexible beam with a prismatic joint" *Transaction of ASME, Journal of Dynamic Systems, Measurement, and Control*, 114, 422-427.
- Tavasoli, A., (2015), "Dynamic modeling and nonlinear boundary control of hybrid Euler-Bernoulli beam system with a tip mass," *Proceedings of the Institution of Mechanical Engineers, Part K: Journal of Multi-Body Dynamics*, 229(1), 3-15.
- Teng, Y.Y., and Cai, G., (2007), "Frequency characteristics of a flexible hub-beam system with arbitrary settling position of attached mass," *Journal of Vibration and Control*, 13(6), 769-794.
- Theodore, R.J., and Ghosal, A., (1995), "Comparison of the assumed modes and finite elements model for flexible multilink manipulators," *The International Journal of Robotics Research*, 14, 91-111.
- Theodore, R.J., and Ghosal, A., (1997), "Modelling of flexible manipulators with prismatic joints," *IEEE Transactions on Systems, Man and Cybernetics-Part B*, 27, 296-305.
- Theodore, R.J., and Ghosal, A., (2003), "Robust control of multilink flexible manipulators," *Mechanism and Machine Theory*, 38, 367-377.
- To, C.W.S., (1982), "Vibration of a cantilever beam with a base excitation and tip mass," *Journal of Sound and Vibration*, 83(4), 445-460.
- Usoro, P.B., Nadira, R., and Mahil, S.S., (1986), "A finite element/Lagrangian approach to modeling lightweight flexible manipulators," *Transaction of ASME, Journal of Dynamic Systems, Measurement, and Control*, 108, 198-205.
- Tohki, M.O., Mohamed, Z., and Shaheed, M.H., (2001), "Dynamic characterization of a flexible manipulator system," *Robotica*, 19, 574-580.
- Wang, F.Y., and Guan, G., (1994), "Influence of rotatory inertia, shear and loading on vibration of flexible manipulator," *Journal of Sound and Vibration*, 171, 483-452.
- Wang, J., Pi, Y., Hu, Y., Zhu, Z., and Zeng, L., (2017), "Adaptive simultaneous motion and vibration control for a multi flexible-link mechanism with uncertain general harmonic disturbance," *Journal of Sound and Vibration*, 408(60-72).
- Wang, L.H., Hu, Z.D., Zhong, Z., and Ju, J.W., (2010), "Dynamic analysis of an axially translating viscoelastic beam with an arbitrarily varying length," *Acta Mechanica*, 214, 225-244.
- Wijk, V., Krut, S., Pierrot, F., and Herder, J.L., (2013), "Design and experimental evaluation of a dynamically balanced redundant planar 4-RRR parallel manipulator," *The International Journal of Robotics Research*, 32(6), 744-759.
- Wu, J., Gao, Y., Zhang, B., and Wang, L., (2017), "Workspace and dynamic performance evaluation of the parallel manipulators in a spray-painting equipment," *Robotics and Computer Integrated Manufacturing*, 44, 199-207.
- Wu, J., Wang, J., Wang, L., and Li T., (2009), "Dynamics and control of a planar 3-DOF parallel manipulator with actuation redundancy," *Mechanism and Machine Theory*, 44(4), 835-849.
- Wu, J., Yu, G., Gao Y., and Wang, L., (2018), "Mechatronics modeling and vibration analysis of a 2-DOF parallel manipulator in a 5-DOF hybrid machine tool," *Mechanism and Machine Theory*, 121, 430-445.
- Wu, S., Haug, E.J., and Kim, S., (2007), "A variational approach to dynamics of flexible multibody systems," *Mechanics of Structures and Machines*, 17(1), 3-32.
- Wu, S., Tang, S., and Huang, K., (2018), "Vibration attenuation of a two-link flexible arm carried by a translational stage," *Journal of Vibration and Control*, First Published March 26.
- Xiao, S., Chen, B., and Du, Q., (2007), "On dynamic behavior of a cantilever beam with tip mass in a centrifugal field," *Mechanics Based Design of Structures and Machines*, 33(1), 79-98.
- Yang, H., Yu, Y., Yuan Y., and Fan, X., (2015), "Back-stepping control of two-link flexible manipulator based on an extended state observer," *Advances in Space Research*, 56, 2312-2322.
- Yeon, J.S., Yim, J., and Park, J.S., (2012), "Robust control using recursive design method for flexible joint robot manipulators," *Journal of Mechanical Science and Technology*, 25(12), 3205-3213.
- Yigit, A., Scott, R.A., and Ulsoy, A.G., (1988), "Flexural motion of a radially rotating beam attached to a rigid body," *Journal of Sound and Vibration*, 121(2), 201-210.
- Yuan, K., (1995), "Regulation of single-link flexible manipulator involving large elastic deflections," *Journal of Guidance, Control, and Dynamics*, 18(3), 635-637.

- Yun, J.N., and Su, J., (2014), "Design of a disturbance observer for a two-link manipulator with flexible joints," *IEEE Transactions on Control Systems Technology*, 22(2), 809-815.
- Yu, S., and Elbestawi, M.A., (1995), "Modelling and dynamic analysis of a two-link manipulator with both joint and link flexibilities," *Journal of Sound and Vibration*, 179, 839-854.
- Zavodney, L.D., and Nayfeh, A.H., (1989), "The non-linear response of a slender beam carrying lumped mass to a principal parametric excitation: theory and experiment," *International Journal of Non-linear Mechanics*, 24, 105-125.
- Zebin, T., (2012), "Modeling and control of a two-link flexible manipulator using fuzzy logic and genetic optimization techniques," *Journal of Computers*, 7(3).
- Zhang, D., (2009), "Recursive Lagrangian dynamic modeling and simulation of multi-link spatial flexible manipulator arms", *Applied Mathematics and Mechanics*, 30(10), 1283-1294.
- Zhang, J.F., (2011), "Dynamic modeling of planar flexible multi-link manipulators with accounting for both link foreshortening and link material damping," *Advanced Materials Research*, 199-200, 19-24.
- Zhang, L., and Liu, J., (2013), "Adaptive boundary control for flexible two-link manipulator based on partial differential equation dynamic model," *IET Control Theory & Applications*, 7(1).
- Zhang, X., Xu, W., and Nair, S., (2004), "Comparison of some modeling and control issues for a flexible two link manipulator," *ISA Transactions* 43, 509-525.
- Zhang, X., Xu, W., Nair, S., and Chellaboina, V., (2005), "PDE modeling and control of a flexible two-link manipulator," *IEEE Transactions on Control Systems Technology*, 13(2).
- Zhang, X., Zhang, D., Chen, S., and Hong, J., (2017), "Modal characteristics of a rotating flexible beam with a concentrated mass based on the absolute nodal coordinate formulation," *Nonlinear Dynamics*, 88, 61-77.
- Zhou, D., (1997), "The vibrations of a cantilever beam carrying a heavy tip mass with elastic supports," *Journal of Sound and Vibration*, 206(2), 275-279.

Books

1. Nayfeh A. H., *Introduction to Perturbation Techniques*, Wiley Interscience, New York, 1981.
2. Nayfeh, A H., Balachandran, B: *Applied Nonlinear Dynamics: Analytical, Computational, and Experimental Methods*, Wiley Interscience, New York(1995).
3. Nayfeh, A.H., and Mook, D.T.: *Nonlinear Oscillations*. Wiley, New York (1995).
4. Ghosal, A.: *Robotics: Fundamental Concepts and Analysis*. Oxford University Press, 2006.
5. Meirovitch, L.: *Analytical Methods in Vibration*. The Macmillan Company, 1967.
6. Meirovitch, L.: *Principles and Techniques of Vibration*. Prentice Hall International, 1997.