

List of Figures

Figure	Title	page
1.1	An induction motor	1
1.2	A stator with stator windings	2
1.3	A squirrel cage rotor	2
1.4	A ball-bearing	2
1.5	Categories of faults in the induction motor	4
1.6	Types of faults in the induction motor	4
1.7	Types of failure modes in a Y-connected stator winding	6
2.1	A schematic of a condition based maintenance system (adapted from [Rai and Upadhyay, 2016])	13
2.2	Techniques used for fault diagnosis of an induction motor	14
2.3	Basic flowchart of the fault diagnosis techniques	15
3.1	Optimal hyperplane separating two classes with maximum margin from support vectors	34
4.1	(a) A typical ball-bearing and (b) its schematic diagram	37
4.2	Experimental set up for recording of current signals with bearing faults in a three-phase induction motor	39
4.3	Set of the bearings with fault in (1) outer-race, (2) inner-race, (3) cage and, (4) ball, at (a) driving-end, (b) fan-end	39
4.4	Block diagram of the proposed methodology for analysis of bearing faults	40
4.5	Current signals for various bearing cases where outer-race ₁ at driving-end and outer-race ₂ at fan-end	40
4.6	Contours based on S-transform for various bearings conditions on driving-end. Highlighted areas depict differences in density of contour plot in various cases.	41
4.7	Contours based on S-transform for various bearings conditions on fan-end. Highlighted areas depict differences in density of contour plot in various cases.	41
4.8	(a) Maximum magnitude plot, (b) Maximum phase angle plot; Standard deviation for (c) Max. magnitude and (d) Max. phase plots for various bearing conditions on driving-end.	42
4.9	(a) Maximum magnitude plot and (b) Maximum phase angle plot; Standard deviation for (c) Max. magnitude and (d) Max. phase plots for various bearing conditions on fan-end.	43
4.10	Experimental set up for the measurement of current signals of induction motor under normal and faulty conditions.	44
4.11	Bearings of Type (a) 6204 and (b) 6205 with (1) ball fault, (2) cage fault, and (2) outer-race fault	44
4.12	FFT of (a) Supply voltage and (b) current signals (healthy and ball fault).	45
4.13	Fault index (<i>FI</i>) for (a) healthy and ball fault and (b) all bearing conditions	45
4.14	Flowchart of the proposed algorithm for detecting the location of faulty bearings	47
4.15	Bearings with Fault-1: Ball fault and Fault-2: Outerrace fault at (a) fan-end and (b) driving-end of the motor	48
4.16	Current signals of bearings with ball fault and outerrace fault present at either fan-end or driving-end	48
4.17	Standard deviation of magnitude of ST matrix with respect to (a) time and (b) frequency axis	49

4.18	Standard deviation of phase angle of ST matrix with respect to (a) time and (b) frequency axis	49
4.19	(a) Variance of each component extracted by PCA, (b) their cumulative variance	49
4.20	Scatter plot of training set using Principal Component 1 against other Principal Components	50
4.21	Fault indexes to locate (a) ball fault, (b) cage fault, and (c) outer-race fault either at fan-end and driving-end.	52
4.22	Fault classification using OAA-SVM	54
4.23	Accuracy for various combinations of four features for classification of ball fault and other faults using SVM1	54
4.24	Accuracy for various combinations of two features for classification of cage fault and outer-race faults using SVM2	55
4.25	Architecture of the ANN used	56
4.26	Flowchart of the proposed algorithm	57
5.1	Experimental set-up to record current signals for stator winding fault diagnosis	60
5.2	Stator current signals for (a) healthy, (b) turn-fault, and (c) ground fault for a three-phase induction motor	62
5.3	FFT of stator current signals of (a) Phase-A, and (b) Phase-B under healthy, turn-fault and ground faults conditions	62
5.4	Block diagram summarizing feature extraction, selection and classification process for stator faults	65
5.5	Standard deviation of ST matrix of stator current signals along frequency axis under ground fault conditions when the fault is in (a) Phase-A, (b) Phase-B, and (c) Phase-C windings	65
5.6	Standard deviation of ST matrix of stator current signals along frequency axis for a healthy, turn-fault and ground fault condition in (a) Phase-A, (b) Phase-B, and (c) Phase-C	67
5.7	Fault index for identifying faults in the stator windings	67
5.8	Fault index for discriminating turn-faults and ground-faults in stator windings	68
5.9	Maximum accuracies for each set of feature combinations (n) for faulty phase detection in case of turn-faults	68
5.10	Maximum accuracies for each set of feature combinations (n) for faulty phase detection in case of ground faults.	69
5.11	Flowchart of the fault diagnosis strategy for stator winding faults	70
6.1	Experimental set-up for recording current signals under healthy and BRB fault conditions	72
6.2	Pictures of the rotor with (a) one BRB and (b) two BRB faults	72
6.3	Current signals for different rotor conditions under full-load case	73
6.4	Contour figures of the ST matrix of stator current signals with (a) healthy, (b) 1BRB fault, and (c) 2BRB fault conditions	73
6.5	Energy of the ST matrix for different loads and various BRB fault conditions	74
6.6	Standard deviation of the energies	75
6.7	The entropy of the ST matrix under different load and BRB fault conditions	75
6.8	The fault index, FI under different load and rotor fault conditions	76